

Delock LTE Antenna SMA plug 1.7 - 2.0 dBi ULA100 1 m omnidirectional fixed outdoor white

Description

This antenna by Delock allows the usage of different LTE bands indoors and outdoors. It is completely compatible to GSM, UMTS, LTE, ZigBee, DECT, Z-Wave, NB-IoT, WLAN, Bluetooth, ISM, DECT, TETRA and LoRa .



Item no. 12545

EAN: 4043619125456

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Technical details

- Connector: 1 x SMA plug
- Frequency range:
 - 698 - 960 MHz
 - 1710 - 2170 MHz
 - 2300 - 2700 MHz
- GSM, UMTS, LTE, Bluetooth, ISM, NB-IoT, LoRa, Z-Wave, WLAN, ZigBee, DECT, TETRA
- Antenna gain:
 - 698 - 960 MHz: 1.7 dBi
 - 1710 - 2170 MHz: 1.7 dBi
 - 2300 - 2700 MHz: 2.0 dBi
- VSWR:
 - 698 - 960 MHz: 6.0
 - 1710 - 2170 MHz: 2.5
 - 2300 - 2700 MHz: 2.5
- Operating temperature: -40 °C ~ 85 °C
- Housing material: polycarbonate
- Protection class: IP67

- Colour: white
- Cable: coaxial
- Cable type: ULA100
- Cable colour: black
- Cable diameter: ca. 2.8 mm
- Cable attenuation: 0.98 dB @ 1500 MHz per meter
- Smallest bending radius: 14 mm
- Cable length incl. connectors: ca. 1 m
- Dimensions (LxD): ca. 77 x 45 mm


System requirements

- Device with a free SMA jack


Package content

- Antenna


Images




Radiation Pattern 698 - 824 MHz




Radiation Pattern 836 - 960 MHz




Radiation Pattern 1710 - 1980 MHz



Radiation Pattern 1990 - 2300 MHz



Radiation Pattern 2400 - 2700 MHz



General

Protection category:	IP67
Suitable for indoor:	yes
Suitable for outdoor:	yes

Interface

connector:	1 x SMA plug
------------	--------------

Technical characteristics

Frequency range:	698 MHz - 960 MHz 2300 MHz - 2700 MHz 1710 MHz - 2170 MHz
Antenna gain:	2 dBi 1.7 dBi
Impedance:	50 Ω
Polarisation:	linear vertical
VSWR:	2.5 6.0

Physical characteristics

Housing material:	Polycarbonat
Cable category:	coaxial
Cable type:	ULA 100
Cable attenuation:	0.98 dB @ 1500 MHz per meter
Cable colour:	black
Cable length incl. connector:	1 m
Diameter:	45 mm
Smallest bending radius:	14 mm
Colour:	white

Thread type:	1/2" - 12 UNC
--------------	---------------

