

# Delock Antenna Cable N plug > RP-SMA plug CFD400 LLC400 10 m low loss

## Description

This high-quality coaxial cable ensures a reliable connection of components of the radio frequency technology. It is characterised by a **very low attenuation**. Thanks to the **waterproof** N connector, this cable is ideal for outdoor use.



10 m

**Item no. 13028**

EAN: 4043619130283

Country of origin: Taiwan,  
Republic of China

Package: Box

## Technical details

- Connectors:
  - 1 x N plug waterproof >
  - 1 x RP-SMA plug
- Impedance: 50 Ohm
- Cable type: CFD400, LLC400
- Cable type: coaxial
- Cable attenuation:
  - 0.3 dB @ 3.0 GHz per meter
  - 0.48 dB @ 6.0 GHz per meter
- Cable diameter: ca. 10.5 mm
- Smallest bending radius: 51.5 mm
- Cable colour: black
- Length incl. connectors (L): ca. 10 m

## System requirements

- Device with one free N and RP-SMA port

## Package content

- Antenna cable

## Images



Trid	SWR	f (Hz)	Ref (U)	Cal (Sm)	Trid	SWR	f (Hz)	Ref (U)	Cal (Sm)
1	1	1000000	1.000	1.000	1	1	1000000	1.000	1.000
2	1.000000	GHz	1.000	1.000	2	1.000000	GHz	1.000	1.000
3	1.000000	GHz	1.000	1.000	3	1.000000	GHz	1.000	1.000
4	1.000000	GHz	1.000	1.000	4	1.000000	GHz	1.000	1.000
5	1.000000	GHz	1.000	1.000	5	1.000000	GHz	1.000	1.000
6	1.000000	GHz	1.000	1.000	6	1.000000	GHz	1.000	1.000
7	1.000000	GHz	1.000	1.000	7	1.000000	GHz	1.000	1.000
8	1.000000	GHz	1.000	1.000	8	1.000000	GHz	1.000	1.000
9	1.000000	GHz	1.000	1.000	9	1.000000	GHz	1.000	1.000
10	1.000000	GHz	1.000	1.000	10	1.000000	GHz	1.000	1.000
11	1.000000	GHz	1.000	1.000	11	1.000000	GHz	1.000	1.000
12	1.000000	GHz	1.000	1.000	12	1.000000	GHz	1.000	1.000
13	1.000000	GHz	1.000	1.000	13	1.000000	GHz	1.000	1.000
14	1.000000	GHz	1.000	1.000	14	1.000000	GHz	1.000	1.000
15	1.000000	GHz	1.000	1.000	15	1.000000	GHz	1.000	1.000
16	1.000000	GHz	1.000	1.000	16	1.000000	GHz	1.000	1.000
17	1.000000	GHz	1.000	1.000	17	1.000000	GHz	1.000	1.000
18	1.000000	GHz	1.000	1.000	18	1.000000	GHz	1.000	1.000
19	1.000000	GHz	1.000	1.000	19	1.000000	GHz	1.000	1.000
20	1.000000	GHz	1.000	1.000	20	1.000000	GHz	1.000	1.000
21	1.000000	GHz	1.000	1.000	21	1.000000	GHz	1.000	1.000
22	1.000000	GHz	1.000	1.000	22	1.000000	GHz	1.000	1.000
23	1.000000	GHz	1.000	1.000	23	1.000000	GHz	1.000	1.000
24	1.000000	GHz	1.000	1.000	24	1.000000	GHz	1.000	1.000
25	1.000000	GHz	1.000	1.000	25	1.000000	GHz	1.000	1.000
26	1.000000	GHz	1.000	1.000	26	1.000000	GHz	1.000	1.000
27	1.000000	GHz	1.000	1.000	27	1.000000	GHz	1.000	1.000
28	1.000000	GHz	1.000	1.000	28	1.000000	GHz	1.000	1.000
29	1.000000	GHz	1.000	1.000	29	1.000000	GHz	1.000	1.000
30	1.000000	GHz	1.000	1.000	30	1.000000	GHz	1.000	1.000

CH1 Start 9 kHz    Pur 10 dBm    Stop 6 GHz

### Interface

Connector 1:	1 x RP-SMA plug
Connector 2:	1 x N male

### Technical characteristics

Impedance:	50 Ω
------------	------

### Physical characteristics

Cable type:	CFD400, LLC400
Cable attenuation:	0.30 dB @ 3.0 GHz 0.48 dB @ 6.0 GHz
Cable colour:	black
Cable length:	10 m
Smallest bending radius:	51.5 mm