

Delock TOSLINK Splitter 1 x TOSLINK in to 2 x TOSLINK out

Description

This splitter by Delock receives an TOSLINK signal from a DVD or Blu-ray player and splits it to two connected amplifiers. Thereby one TOSLINK connection can be used to operate two TOSLINK devices.



Item no. 18766

EAN: 4043619187669

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - Input:
 - 1 x TOSLINK female S/PDIF
 - 1 x DC 5 V power connector
 - Output:
 - 2 x TOSLINK female S/PDIF
- Supported sample rates: 32 / 44.1 / 48 / 96 / 192 kHz
- Bit rate 16 - 24 Bit
- Supports all common 2.0 and 5.1 audio formats:
 - LPCM, Dolby Digital, DTS Audio
- Metal housing
- Colour: black
- Dimensions (LxWxH): ca. 50 x 41 x 21 mm

Power supply specification

- Wall power supply

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
inside: \varnothing ca. 2.1 mm
outside: \varnothing ca. 5.5 mm
length: ca. 9 mm

System requirements

- Digital optical audio signal

Package content

- TOSLINK splitter
- External power supply

Images



Interface

Output:	2 x TOSLINK female S/PDIF
Input:	1 x TOSLINK female S/PDIF 1 x 5 V DC female 5,5 mm x 2,1 mm

Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	50 mm
Width:	41 mm
Height:	21 mm