

Delock TOSLINK Switch 2 x TOSLINK in to 1 x TOSLINK out

Description

With this TOSLINK switch by Delock up to two TOSLINK devices can be used with one TOSLINK amplifier. With the button on the device you can switch between the TOSLINK devices.



Item no. 18767

EAN: 4043619187676

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - Input:
 - 2 x TOSLINK female S/PDIF
 - 1 x DC 5 V power connector
 - Output:
 - 1 x TOSLINK female S/PDIF
- Supported sample rates: 32 / 44.1 / 48 / 96 / 192 kHz
- Bit rate 16 - 24 Bit
- Supports all common 2.0 and 5.1 audio formats:
 - LPCM, Dolby Digital, DTS Audio
- Metal housing
- Colour: black
- Dimensions (LxWxH): ca. 50 x 41 x 21 mm

Power supply specification

- Wall power supply

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
inside: ø ca. 2.1 mm
outside: ø ca. 5.5 mm
length: ca. 9 mm


System requirements

- Digital optical audio signal

Package content

- TOSLINK switch
- External power supply

Images



Interface

Output:	1 x TOSLINK female S/PDIF
Input:	1 x 5 V DC female 5,5 mm x 2,1 mm 2 x TOSLINK female S/PDIF

Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	50 mm
Width:	41 mm
Height:	21 mm