

# Delock External USB Type-C™ Combo Enclosure for M.2 NVMe PCIe or SATA SSD - tool free

## Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD or SATA M.2 SSD** in 2280, 2260, 2242 and 2230 format. It can be connected directly via USB-C™ plug to the PC or laptop.

### Combo enclosure

The big advantage of this Delock M.2 enclosure is that both SATA and PCIe (NVMe) M.2 SSDs can be inserted into the enclosure. The memory is **automatically recognized** by the chipset and can then be used.

### SSD installation without tools

The special feature of this enclosure is that no tools are required to install the M.2 SSD. The lid is pushed backwards and the SSD is plugged into the slot, the SSD will be attached to the PCB with a rubber nipple and then the lid is reattached until it locks.



**Item no. 42635**

EAN: 4043619426355

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - external: 1 x USB 10 Gbps USB Type-C™ male
  - internal: 1 x M.2 key M slot
- Chipset: Realtek RTL9210B
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on SATA or PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Bootable
- Supports UASP
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Lanyard strip for cap
- Dimensions (LxWxH): ca. 115 x 30 x 11 mm

- Hot Plug, Plug & Play

---

## System requirements

- Chrome OS 83.0 or above
- Linux Kernel 3.18 or above
- Mac OS 10.15.5 or above
- Windows 8.1/8.1-64/10/10-64/11
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port

---

## Package content

- External enclosure M.2
- User manual

---

## Images



## General

Function:	NVM Express (NVMe) Plug & Play
Supported operating system:	Chrome OS 83.0 or above Linux Kernel 3.18 or above Mac OS 10.15.5 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported module:	Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on SATA or PCIe (NVMe)
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

## Interface

External:	1 x USB 10 Gbps USB Type-C™ male
Internal:	1 x 67 pin M.2 key M slot

## Technical characteristics

Chipset:	Realtek RTL9210B
Data transfer rate:	up to 10 Gbps

## Physical characteristics

Housing material:	Plastic
Length:	115 mm
Width:	30 mm
Height:	11 mm