

Delock SATA 6 Gb/s Flash Module 2 GB vertical SLC

Description

The Delock SATA 6 Gb/s flash module is, due to its small size and high shock resistance, ideally suited for usage in mobile devices such as IPCs and measuring systems, as well as for the digital signage range. The module supports the SATA 6 Gb/s standard and is therefore convenient for applications that require fast read and write speeds. The metal clip at the SATA connector enables the module to snap in to your SATA port.



2 GB

Item no. 54351

EAN: 4043619543519

Country of origin: Taiwan,
Republic of China

Package: Antistatic cover

Technical details

- Capacity: 2 GB
- Memory chip: SLC (Single Level Cell)
- 7 pin SATA 6 Gb/s interface
- Transmission modes: SATA 6 Gb/s, SATA 3 Gb/s, SATA 1.5 Gb/s
- Operating voltage: 5 V +/- 5%
- Operating temperature: 0 °C ~ +70 °C
- Storage temperature: -55 °C ~ +95 °C
- Endurance:
 - Maximum write cycles: 6000
 - Read: unlimited
- 24 MB/s read, 18 MB/s write
- Power consumption:
 - Read: 120 mA
 - Write: 130 mA
 - Idle: 100 mA
- MTBF: > 3.000.000 hrs.
- Vibration: 20 G, 7 ~ 2000 Hz
- Shock: 1,500 G / 0.5 ms
- Dimensions (LxWxH): ca. 39.55 x 20.9 x 8 mm

System requirements

- A free SATA 7 pin port
- Power supply with a free Molex power connector

Package content

- SATA Flash module
- Power cable

Images

