

Delock Digital Audio Converter Coaxial > TOSLINK

Description

The Delock audio converter converts a coaxial S/PDIF audio signal into an optical S/PDIF signal. A device with a coaxial digital output can be connected to a device with a TOSLINK input.



Item no. 62790

EAN: 4043619627905

Country of origin: China

Package: Box

Technical details

- Connector:
 - Input:
 - 1 x Coaxial female S/PDIF
 - 1 x USB Type Micro-B female (5 V power supply)
 - 1 x DC 3.5 x 1.35 mm female (5 V power supply)
 - Output:
 - 1 x TOSLINK female S/PDIF
- Supported sample rates: 44.1 / 48 / 96 / 192 kHz
- Supports Dolby Digital and DTS 5.1 Audio
- Robust metal housing
- Dimensions (LxWxH): ca. 63 x 53 x 23 mm

System requirements

- A free S/PDIF female port
- Connection cables
- A free USB Type-A female port

Package content

- Converter Coaxial > TOSLINK
- USB Type-A to Type Micro-B cable, length ca. 1 m

Images



General

Specification:	DTS Audio Dolby Digital LPCM
----------------	------------------------------------

Interface

Output:	1 x TOSLINK female
Input:	1 x Coaxial female S/PDIF 1 x 5 V DC jack 3.5 mm x 1.35 mm 1 x USB 2.0 Type Micro-B female

Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	63 mm
Width:	53 mm
Height:	23 mm