

Delock Audio Converter Digital > Analogue HD

Description

The audio converter by Delock converts a digital audio signal into an analogue stereo signal. For example a DVD or Blu-ray player can be connected to the input of the device and the signal can be supplied via optical TOSLINK or via S/PDIF coaxial connection. At the output port, the audio signal is transmitted via the RCA connection.



Item no. 63477

EAN: 4043619634774

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - Input:
 - 1 x TOSLINK female S/PDIF
 - 1 x Coaxial female S/PDIF
 - 1 x USB Type Micro-B female (5 V power supply)
 - Output:
 - 2 x RCA female
- Chipset: MS8416
- Supported sample rates: 32 / 44.1 / 48 / 96 / 192 kHz
- Bit rate 16 - 24 Bit
- Plastic housing
- Colour: black
- Dimensions (LxWxH): ca. 63 x 44 x 23 mm


System requirements

- Digital audio signal
- Power source with a free USB Type-A female port

Package content

- Converter digital > analogue
- USB Type-A to Type Micro-B cable, length ca. 30 cm
- User manual

Images



Interface

Output:	2 x RCA female (red, white)
Input:	1 x Coaxial female S/PDIF 1 x TOSLINK female S/PDIF 1 x USB Type Micro-B female

Physical characteristics

Housing colour:	black
Housing material:	Plastic
Length:	63 mm
Width:	44 mm
Height:	23 mm