

# Delock USB 3.0 Dual Docking Station for 2 x SATA HDD / SSD with Clone and Erase Function in Metal Housing

## Description

This HDD / SSD Docking Station in metal frame by Delock enables an external connection of two 2.5" or 3.5" SATA HDDs / SSDs through the USB interface. This solution does not require an external enclosure since the HDD / SSD will be plugged into the docking station directly. Furthermore, the clone function enables to copy the content of one HDD to another without using a PC. By the help of the erase function, the data of the inserted memory can be deleted with 3 different modes.



**Item no. 63992**

EAN: 4043619639922

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 2 x SATA 6 Gb/s 22 pin receptacle
  - 1 x USB 3.0 Type-B female
  - 1 x DC jack
- Chipset: JMicron JMS561U
- Function key:
  - 1 x clone / erase button
  - 1 x On / Off switch
- For 2.5" and 3.5" SATA HDD / SSD
- Suitable for all SATA HDDs / SSDs up to SATA 6 Gb/s
- Data transfer rate up to:
  - SuperSpeed 5 Gb/s,
  - Hi-Speed 480 Mb/s,
  - Full-Speed 12 Mb/s,
  - Low-Speed 1.5 Mb/s
- 2 x eject button
- LED indicator for power, access, copy and erase status

- Dimensions (LxWxH): ca. 151 x 109 x 59 mm
  - Plug & Play
- 

## Power supply specification

- Wall power supply
  - Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1 A
  - Output: 12 V / 3 A
  - Ground outside, plus inside
  - Dimensions:
    - inside:  $\varnothing$  ca. 2.1 mm
    - outside:  $\varnothing$  ca. 5.5 mm
    - length: ca. 12.0 mm
- 

## System requirements

- Chrome OS
  - Linux Kernel 4.9.4 or above
  - Mac OS 10.13.6 or above
  - Windows 7/7-64/8.1/8.1-64/10/10-64
  - PC or laptop with a free USB Type-A port
- 

## Package content

- Dual Docking Station
- 1 x cable USB 3.0 A male to USB 3.0 B male, length ca. 1 m
- External power supply
- User manual

## Images



## General

|                             |   |
|-----------------------------|---|
| Function:                   | Plug & Play<br>Clone Function<br>Erase function   |
| Suitable for data medium:   | 2.5"<br>3.5"<br>SSD or HDD  |
| Supported operating system: | Chrome OS<br>Linux Kernel 4.9.4 or above<br>Mac OS 10.13.6 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 7 32-Bit<br>Windows 7 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |

## Interface

|           |   |
|-----------|---|
| External: | 1 x DC 12 V power connector<br>1 x USB 5 Gbps Type-B female |
| Internal: | 2 x SATA 22 Pin Buchse                                      |

## Technical characteristics

|          |                 |
|----------|-----------------|
| Chipset: | Prolific PL2773 |
|----------|-----------------|

## Physical characteristics

|                   |        |
|-------------------|--------|
| Housing material: | metal  |
| Length:           | 151 mm |
| Width:            | 109 mm |
| Height:           | 59 mm  |
| Colour:           | black  |