

Delock External USB 3.1 2 Port Type-A and 2 Port USB Type-C[™] Hub with 10 Gbps

Description

This USB Hub by Delock can be connected to a computer via the USB Type-CTM interface. It expands the computer by**two USB Type-**A ports and **two USB-CTM** ports.

USB Power Delivery support up to 60 watt

On the USB-C[™] "PD/USB 3.1" port, a support with up to 60 watts of charging power is available.

With a USB-C[™] power supply, laptops such as the MacBook or Chromebook can be charged during operation. To do this, the power supply from the laptop have to be connected to the USB Type-C[™] PD port on the front of the hub.

The included power supply provides power to the connected devices on the front. The hub can also be used without a power supply.



Item no. 64054

EAN: 4043619640546 Country of origin: China Package: Retail Box

Technical details

- Connectors:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
 - 2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ Power Delivery female
- 1 x DC 5 V power connector
- Chipset: Realtek RTS5429
- Data transfer rate up to:

SuperSpeed USB 10 Gbps, SuperSpeed USB 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

- Output power for host: max. 60 W
- 1 x LED indicator
- Colour: black
- Dimensions (LxWxH): ca. 92 x 54 x 19 mm
- Plug & Play

DATASHEET



Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.4 A
- Output: 5 V / 2 A
- Ground outside, plus inside
- Dimensions: inside: ø ca. 2.5 mm outside: ø ca. 5.5 mm length: ca. 10 mm

System requirements

- Chrome OS
- Linux Kernel 4.6 or above
- Mac OS 10.13.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C[™] port

Package content

- Hub USB
- 1 x Cable USB-C[™] male to USB-C[™] male, length ca. 60 cm
- Power supply
- User manual

Images



DATASHEET



General

Function:	Plug & Play
Specification:	USB 10 Gbps
Supported operating system:	Chrome OS Linux Kernel 4.6 or above Mac OS 10.13.3 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	1 x

Interface

Connector 1:	1 x USB 10 Gbps USB Type-C™ female
Connector 2:	2 x USB 10 Gbps Type-A female
connector 3:	2 x USB 10 Gbps USB Type-C™ female
connector 4:	1 x 5 V DC jack

Technical characteristics

Chipset:	Realtek RTS5429
Data transfer rate:	10 Gbps

Physical characteristics

Length:	92 mm
Width:	54 mm
Height:	19 mm
Colour:	black

Power supply

DATASHEET



Input:	AC 100 - 240 V / 50 - 60 Hz / 0.4 A
Output:	5 V / 2 A
Connector:	DC plug 5.5 mm x 2.5 mm