

Delock HDMI Receiver for Video over IP

Description

This video extender system by Delock allows video signals to be transmitted over an IP network. The transmitter and receiver can be connected with a network cable of up to 100 m. Alternatively both devices can be connected via a switch, the distance between the source and the display device can then be 200 m.



HDBiT

The HDBiT technology allows different transmitters and receivers to be combined with each other, e.g. a DisplayPort transmitter with an HDMI receiver. Optionally, several receivers can be operated simultaneously.

Item no. 65951

EAN: 4043619659517

Country of origin: China

Package: White Box

Technical details

- Connectors:
 - 1 x RJ45 jack
 - 1 x HDMI-A 19 pin female
 - 1 x 3.5 mm 3 pin stereo jack female (IR)
 - 1 x DC 5.5 x 2.1 mm female
- Transmission of audio and video signals
- Transmission of IR signals 20 - 60 kHz
- Supported resolution: 480i / 480p / 576i / 576p / 720p / 1080i / 1080p
- Supports EDID und HDCP
- Supports RTP Multicast
- Supports One-to-one and One-to-many connections
- Latency: ca. 400 ms
- Power consumption: max. 3.5 W
- Robust metal housing
- Wallmount option
- Dimensions (LxWxH): ca. 97 x 94 x 24 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.2 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: \varnothing ca. 2.1 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 9 mm

System requirements

- Connection cables
- Transmitter for Video over IP
- Switch with VLAN or IGMP snooping

Package content

- HDMI receiver
- Infrared receiver
- Power supply
- User manual

Images



General

Mounting type:	Wall mounting
----------------	---------------

Interface

connector:	1 x RJ45 jack
Connector 1:	1 x HDMI-A female
connector 3:	1 x DC jack
connector 4:	1 x 3.5 mm 3 pin stereo jack female

Technical characteristics

Maximum screen resolution:	1080p
----------------------------	-------

Physical characteristics

Housing colour:	black
Housing material:	metal