

# Delock DIP sliding switch 10-digit 2.54 mm pitch THT vertical red 5 pieces

## Description

This DIP sliding switch by Delock is suitable for the through-hole mounting on a PCB.

## **THT Assembly Technology**

The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

### **Multifunctional application**

The DIP switch is mainly used in telecommunications, computers and measuring.



5 x

#### Item no. 66070

EAN: 4043619660704 Country of origin: China

Package: Tube

#### **Technical details**

• Connectors:

2 x 10 soldering pin

• Number of positions: 10

• Pitch: 2.54 mm

• Switch position: on / off

• Switching rating: 25 mA, 24 VDC

• Insulation resistance: 100 M $\Omega$  / 500 VDC

• Withstanding voltage: 300 VAC / 1 minute

• Soldering temperature: 250 °C for ca. 3 - 5 seconds

• Environmental temperature: -40 °C ~ 85 °C

• Operating temperature: -20 °C ~ 85 °C

· Material: plastic

· Colour: red

Dimensions (LxWxH): ca. 26.8 x 9.9 x 5.6 mm




# Package content

• 5 x DIP sliding switch

# **Images**











## General

e: Soldering
--------------

## Interface

2 x 10 soldering pin connector:

## **Technical characteristics**

Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-20 °C ~ 85 °C
Resistor:	100 MΩ / 500 VDC

# **Physical characteristics**

Pitch distance:	2.54 mm
Material:	Plastic
Length:	26.8 mm
Width:	9.9 mm
Height:	5.6 mm
Switch:	On / Off
Colour:	red