

Delock DIP flip switch piano 6-digit 2.54 mm pitch THT vertical blue 2 pieces

Description

This DIP flip switch by Delock is suitable for the through-hole mounting on a PCB.

THT Assembly Technology

The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

Multifunctional application

The DIP switch is mainly used in telecommunications, computers and measuring.



Item no. 66140

EAN: 4043619661404 Country of origin: China

Package: Tube

Technical details

• Connectors:

2 x 6 soldering pin

Number of positions: 6

• Pitch: 2.54 mm

• Switch position: on / off

Switching rating: 25 mA, 24 VDC

• Insulation resistance: 100 M Ω / 500 VDC

• Withstanding voltage: 300 VAC / 1 minute

• Soldering temperature: 250 °C for ca. 3 - 5 seconds

• Environmental temperature: -40 °C ~ 85 °C

• Operating temperature: -20 °C ~ 85 °C

· Material: plastic

· Colour: blue

Dimensions (LxWxH): ca. 16.8 x 10.8 x 9.4 mm






Package content

• 2 x DIP flip switch

Images











General

Interface

2 x 6 soldering pin connector:

Technical characteristics

Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-20 °C ~ 85 °C
Resistor:	100 MΩ / 500 VDC

Physical characteristics

Pitch distance:	2.54 mm
Material:	Plastic
Length:	16.8 mm
Width:	10.8 mm
Height:	9.4 mm
Switch:	On / Off
Colour:	blue