

# Delock Slot bracket 1 x 19 pin USB 3.0 pin header female internal > 2 x USB 3.0 Type-A female external Low Profile

## Description

This slot bracket by Delock expands the PC by two USB 3.0 Type-A female ports and can be mounted in Mini PCs due to the low profile bracket. The cable of the slot bracket can be connected internally to the motherboard with a 19 pin USB 3.0 pin header. Thus the internal connection will be lead outside, in order to connect devices with USB Type-A connector to the computer.



40 cm

**Item no. 82976**

EAN: 4043619829767

Country of origin: China

Package: Zip poly bag

## Technical details

- Connector:
  - internal: 1 x 19 pin USB 3.0 pin header female
  - external: 2 x USB 3.0 Type-A female
- For the installation in a low profile PC
- Pitch distance: 2.00 mm
- Screw type: #4-40 UNC
- Cable gauge:
  - 30 AWG data line
  - 28 AWG power line
- Cable diameter: ca. 7 mm
- Data transfer rate up to 5 Gbps
- Slot bracket: low profile
- Cable colour: blue
- Cable length without connector: ca. 40 cm

## System requirements

- PC with a free low profile slot
  - Mainboard with a free 19 pin USB 3.0 pin header male
- 

## Package content

- Slot bracket

### Interface

External:	2 x USB 5 Gbps Type-A female
Internal:	1 x 19 pin USB 5 Gbps pin header female

### Technical characteristics

Data transfer rate:	5 Gbps
---------------------	--------

### Physical characteristics

Pitch distance:	2.00 mm
Cable colour:	blue
Cable length:	40 cm
Conductor gauge:	30 AWG data line 28 AWG power line
Screw type:	#4-40 UNC
Slot bracket:	Low Profile