

Delock Slot bracket SATA 6 Gb/s 7 pin receptacle + SATA 15 pin power plug internal > SATA male pin 8 power external

Description

With this slot bracket by Delock e.g. a SATA DOM memory with SATA pin 8 power connector can be connected to the PC externally. The power supply is provided by the SATA 15 pin plug.



Item no. 84951

EAN: 4043619849512 Country of origin: China Package: Zip poly bag

Technical details

- · Connectors:
- 1 x SATA 6 Gb/s 7 pin receptacle +
- 1 x SATA 15 pin power plug >
- 1 x SATA 6 Gb/s plug pin 8 power with latchtype
- E.g. for SATA DOM memories (e.g. for Delock item 54776)
- Data transfer rate up to 6 Gb/s
- Downwards compatible to SATA 1.5 Gb/s and 3 Gb/s
- Voltage: 5 V
- · Cable gauge:
- 26 AWG data line
- 18 AWG power line
- Cable diameter: ca. 2.2 mm
- Cable length without connectors:

SATA data cable: ca. 60 cm

SATA power cable: ca. 30 cm

System requirements

- PC with one free slot
- Power supply with a free SATA power connector
- A free SATA 7 pin plug on the motherboard



Package content

- Standard slot bracket
- Low profile slot bracket for exchange

Images





General

Charification: CATA 6 Ch/a	
Specification: SATA 6 Gb/s	

Interface

Connector 1:	1 x SATA 15 pin plug 1 x SATA 6 Gb/s 7 pin receptacle
Connector 2:	1 x SATA 6 Gb/s 8 pin plug

Technical characteristics

Data transfer rate:	6 Gb/s
Voltage:	5 V

Physical characteristics

Conductor gauge:	26 AWG data line 18 AWG power line
Length:	30 cm 60 cm