

# Delock Cable USB 3.1 Gen 2 key A 20 pin male > USB 3.1 Gen 2 Type-A female panel-mount 70 cm

## Description

This cable by Delock can be connected to the internal USB 3.1 Gen 2 key A socket of a motherboard or a PCI Express card (e.g. [Delock 89603](#)) and can be used to extend a USB connection. The USB Type-A connector can be attached with two screws, e.g. on a slot bracket or a chassis with the corresponding recess. In this way, it is possible to install a USB port in an easily accessible position.



70 cm

**Item no. 85325**

EAN: 4043619853250

Country of origin: China

Package: Zip poly bag

## Technical details

- Connectors:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) key A 20 pin male 90° angled >
  - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
- Two mounting holes for screws, spacing 31 mm, with M3 thread
- Cable gauge:
  - 28 + 30 AWG data line
  - 26 + 28 AWG power line
- Resistor: 5.1 kΩ
- Cable diameter: ca. 6 mm
- Data transfer rate up to:
  - SuperSpeed USB 10 Gbps,
  - SuperSpeed USB 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- Length incl. connectors: ca. 70 cm


## System requirements

- PC with a free USB 3.1 Gen 2 key A interface
- 

## Package content

- USB cable
- 

## Images



## Interface

Connector 1:	1 x USB 3.2 Gen 2 key A 20 pin male
Connector 2:	1 x USB 10 Gbps Type-A female

## Technical characteristics

Data transfer rate:	SuperSpeed USB 10 Gbps
Resistor:	5.1 kΩ

## Physical characteristics

Conductor gauge:	28 AWG data line 30 AWG data line 26 AWG power line 28 AWG power line
Length:	70 cm