

Delock Cable mini DisplayPort 1.2 male with screw > HDMI male 4K Active black 1 m

Description

This cable enables you to connect a HDMI monitor through a free mini DisplayPort interface. The cable supports a resolution up to Ultra HD (4K) and is backward compatible to Full-HD 1080p. The screw of the mini DisplayPort connector secures the connection and prevents accidental unplugging of the cable.



Item no. 85642

EAN: 4043619856428

Country of origin: China

Package: Zip poly bag

Technical details

- Connector:
mini DisplayPort 20 pin male with screw >
HDMI-A 19 pin male
- Input = mini DisplayPort; Output = HDMI
- Screw type: #4-40, thread type UNC, thread class 3A, American Standard Screw
- Chipset: Parade PS176
- DisplayPort 1.2 and High Speed HDMI specification
- Cable gauge: 32 AWG
- Cable diameter: ca. 5.5 mm
- Gold-plated connector
- Active cable, for graphics cards with DP and DP++ output
- Transfer of audio- and video signals
- Supports a resolution up to 4K (4096 x 2160 pixel @ 24 Hz or 3840 x 2160 pixel @ 30 Hz) - depending on the system and the connected hardware
- Supports 3D displays (1080p @ 120 Hz)
- Supports HDCP 1.3
- Supports Eyefinity
- Audio input formats: 8-channel LPCM, compressed audio (AC-3, DTS) and HBR audio format up to 24 Bit audio sample size and 192 kHz sample rate

- 2 x ferrite core
 - Cable length: ca. 1 m (incl. connector)
 - Colour: black
 - OS independent, no driver installation necessary
-

System requirements

- A free mini DisplayPort female port
-

Package content

- Cable mini DisplayPort to HDMI
-

Images



General

Specification:	DisplayPort 1.2 High Speed HDMI HDCP 1.3
----------------	--

Interface

Connector 1:	1 x mini DisplayPort male
Connector 2:	1 x HDMI-A male

Technical characteristics

Chipset:	Parade PS176
Maximum screen resolution:	3840 x 2160 @ 30 Hz

Physical characteristics

Ferrite core:	2 x
Pin finishing:	gold-plated
Conductor gauge:	32 AWG
Screw type:	#4-40 UNC
Length:	1 m
Colour:	black