

Delock Modular Wall Outlet flush mount 2 Port Cat.6 LSA

Description

This network wall outlet by Delock can be installed in-wall or on a back box with 60 mm mounting holes. The LSA blocks can be used with a punch down tool; the horizontal cable feed allows a flexible installation.



Item no. 86125

EAN: 4043619861255

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
external: 2 x RJ45 jack
internal: 2 x LSA block
- Cat.6 specification
- Shielded (STP)
- TIA-568A/B pinout
- Cable diameter up to 0.644 mm (22 - 26 AWG)
- Material: zinc die cast
- Integrated name plate
- Design suitable central plate 50 x 50 mm
- Mounting holes 60 mm
- Colour: pure white RAL 9010
- Dimensions (LxWxH): ca. 80 x 80 x 39 mm

Package content

- Modular Wall Outlet

- 2 screws

Images



General

Suitable for conductor gauge:	22 - 26 AWG
Mounting type:	in-wall

Interface

External:	2 x RJ45 jack
Internal:	2 x LSA block

Technical characteristics

Category:	Cat.6
-----------	-------

Physical characteristics

Housing colour:	white
Length:	80 mm
Width:	80 mm
Height:	39.1 mm