

Delock 2 Port VGA Audio and Video Splitter 450 MHz

Description

This Delock VGA splitter can be used to split the video and audio signal from output of your PC or laptop. Thus you can connect two monitors to one VGA port.



Item no. 87654

EAN: 4043619876549

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Technical details

- Connectors:
 - Input:
 - 1 x VGA 15 pin male
 - 1 x 3.5 mm 3 pin stereo jack female
 - 1 x DC jack
 - Output:
 - 2 x VGA 15 pin female
 - 2 x 3.5 mm 3 pin stereo jack female
- Supports: SVGA, VGA, XGA, SXGA, UXGA, QXGA and Multi-Sync monitors
- Resolution: max. 2048 x 1536 @ 86 Hz
- Supports stereo audio
- VGA bandwidth: 450 MHz
- Supported cable length: up to 55 m
- Daisy Chain (cascadable)
- Plug & Play
- OS independent, no driver installation necessary
- Metal housing
- Dimensions (LxWxH): ca. 163 x 77 x 25 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.12 A
- Ausgang: 5 V / 0,85 ~ 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9.5 mm

System requirements

- PC or laptop with a free VGA port, for the audio transmission it will need an additional a free 3.5 mm Stereo jack
- VGA connection cables

Package content

- VGA Splitter
- Power supply
- User manual

Images

