

# Delock Thunderbolt™ 3 Docking Station 5K - HDMI / USB 3.0 / USB-C™ / SD / LAN

## Description

This Thunderbolt™ 3 docking station by Delock can be connected to a computer with a Thunderbolt™ 3 port and provides a variety of interfaces. The Thunderbolt™ 3 port supports a resolution up to 5K and is compliant to USB, therefore it is possible to connect all USB Type-C™ devices. Two 4K monitors can be operated simultaneously at the Thunderbolt™ 3 and HDMI outputs. Five built-in USB Type-A ports allow the use of peripherals. Connections for a headset and gigabit network, as well as an SD card reader, complete the features. A connected laptop such as the Macbook or Chromebook will be charged during operation.

## Note

Only one additional external monitor can be connected to MacBook devices with M1, M2 and M3 chipset. MacBook devices with M1 Pro, M2 Pro, M3 Pro and M3 Max chipset can connect two or more additional external monitors. Further information is available at [www.apple.com](http://www.apple.com).



5K



**Item no. 87725**

EAN: 4043619877256

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - front side:
    - 1 x USB 3.0 Type-A female
    - 1 x USB 3.0 Type-A female - Battery Charging specification BC1.2
    - 1 x SD / SDHC / SDXC slot
    - 1 x Headset 3.5 mm 4 pin jack
  - back side:
    - 1 x Thunderbolt™ 3 female (connection to computer)
    - 1 x Thunderbolt™ 3 female
    - 1 x HDMI-A 19 pin female
    - 3 x USB 3.0 Type-A female
    - 1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack
    - 1 x DC jack

- Video outputs supports: extended and mirror
  - Resolution up to:  
Windows:  
1 x 5120 x 2880 @ 60 Hz (depending on the system and the connected hardware)  
2 x 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)  
Mac:  
2 x 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
  - Transmission of audio and video signals
  - Output power for host: max. 60 W
  - Metal housing
  - Rubber pads for safe grip and secure stand
  - Colour: silver
  - Dimensions (LxWxH): ca. 230 x 87 x 27 mm
- 

## Power supply specification

- Wall power supply
  - Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1.8 A
  - Output: 20 V / 6.75 A
  - Ground outside, plus inside
  - Dimensions:  
inside:  $\varnothing$  ca. 2.5 mm  
outside:  $\varnothing$  ca. 5.5 mm  
length: ca. 10 mm
- 

## System requirements

- Windows 8.1/8.1-64/10/10-64, Mac ex OS 10.12
  - PC or laptop with a free Thunderbolt™ 3 port
- 

## Package content

- Thunderbolt™ 3 docking station
- Thunderbolt™ 3 cable, length ca. 50 cm
- Power supply
- User manual

## Images



## General

|                             |   |
|-----------------------------|---|
| Function:                   | Battery Charging BC1.2  |
| Supported operating system: | Mac OS 10.12 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |
| Supported memory card:      | SD<br>SDHC<br>SDXC  |

## Interface

|         |   |
|---------|---|
| Output: | 1 x 3.5 mm 4 pin stereo jack female<br>1 x RJ45 jack<br>1 x HDMI-A female<br>1 x SD slot<br>1 x USB 5 Gbps Type-A female - Battery Charging specification BC1.2<br>4 x USB 5 Gbps Type-A female<br>1 x DC jack<br>1 x Thunderbolt™ 3 female |
| Input:  | 1 x Thunderbolt™ 3 USB Type-C™ 24 pin male  |

## Technical characteristics

|                            |                     |
|----------------------------|---------------------|
| Maximum screen resolution: | 5120 x 2880 @ 60 Hz |
| Signal transmission:       | video<br>audio      |

## Physical characteristics

|                   |        |
|-------------------|--------|
| Housing material: | metal  |
| Length:           | 230 mm |
| Width:            | 87 mm  |
| Height:           | 27 mm  |
| Colour:           | silver |

### Power supply

|            |                                     |
|------------|-------------------------------------|
| Type:      | Euro wall power supply              |
| Input:     | AC 100 ~ 240 V / 50 ~ 60 Hz / 1.8 A |
| Output:    | 20 V / 6.75 A                       |
| Connector: | DC plug 5.5 mm x 2.5 mm             |