

# Delock WLAN 802.11 b/g/n Antenna RP-SMA plug 9 dBi omnidirectional with tilt joint black

## Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.



**Item no. 88450**

EAN: 4043619884506

Country of origin: Taiwan,  
Republic of China

Package: Retail Box

## Technical details

- Connector: RP-SMA plug
- Frequency range: 2.400 - 2.500 GHz
- Antenna gain: 9 dBi
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 2.0
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS
- Colour: black
- Length:
  - ca. 384.10 mm (with tilt joint)
  - ca. 352.10 mm (without tilt joint)
- Diameter:
  - ca. 12.60 mm (top)
  - ca. 13.50 mm (RP-SMA)

## System requirements

- Device with a free RP-SMA jack
- 

## Package content

- WLAN antenna
- 

## Images



## Interface

connector:	RP-SMA plug
------------	-------------

## Technical characteristics

Frequency range:	2.400 GHz - 2.500 GHz
Gain:	9 dBi
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	2.0

## Physical characteristics

Housing material:	ABS
Diameter:	12.60 mm
Diameter connector:	13.50 mm
Length with tilt joint:	384.10 mm
Length without tilt joint:	352,10 mm
Colour:	black