

Delock WLAN 802.11 ac/a/h/b/g/n Antenna RP-SMA plug 3 - 5 dBi omnidirectional with tilt joint black

Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.

Bluetooth



Item no. 88898

EAN: 4043619888986

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Technical details

- Connector: RP-SMA plug
- Frequency range:
2.4000 - 2.4835 GHz
5.1500 - 5.8750 GHz
- Antenna gain:
3 dBi @ 2.4000 - 2.4835 GHz
5 dBi @ 5.1500 - 5.8750 GHz
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 2.0
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS
- Colour: black
- Length:
ca. 182.00 mm (with tilt joint)
ca. 150.40 mm (without tilt joint)
- Diameter:
ca. 19.30 mm (top)

ca. 21.60 mm (max.)
ca. 13.50 mm (RP-SMA)









System requirements

- Device with a free RP-SMA jack

Package content

- WLAN antenna

Images



Interface

connector:	RP-SMA plug
------------	-------------

Technical characteristics

Frequency range:	2.4000 GHz - 2.4835 GHz 5.150 - 5.875 GHz
Gain:	3 dBi @ 2.4000 - 2.4835 GHz 5 dBi @ 5.1500 - 5.8750 GHz
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	2.0

Physical characteristics

Housing material:	ABS
Diameter connector:	13.50 mm
Length with tilt joint:	182.00 mm
Length without tilt joint:	150.40 mm
Colour:	black