


# Delock PCI Express Card > 1 x internal M.2 NGFF, 1 x internal mSATA, 1 x internal MiniPCle

## Description

The PCI Express card by Delock expands your PC by one M.2 NGFF slot as well as one mSATA slot and one MiniPCle slot. You can connect to the card M.2 NGFF modules in format 2280, 2260 or 2242. Depending on the M.2 module is SATA based or USB based you should connect the SATA or USB connector with you mainboard. The mSATA module can be connected to the top side, you also should connect the SATA or USB connector to your mainboard. The MiniPCle module can be connected to the bottom side and works over the PCIe interface.



**Item no. 89380**

EAN: 4043619893805

Country of origin: Taiwan,  
Republic of China

Package: White Box

## Special features

- 3 in 1 - Mini PCIe, mSATA slot and M.2 slot
- All Slots are used simultaneously.
- Even without PCIe self-sufficiently

## Technical details

- Connector:
  - 1 x 67 pin M.2 NGFF key B slot
  - 1 x mSATA slot (full size / half size)
  - 1 x MiniPCle slot (full size / half size)
  - 2 x SATA 7 pin (for modules based on SATA, M.2 and mSATA)
  - 1 x 9 pin USB 2.0 pin header (for modules based on USB, M.2 and mSATA)
  - 1 x PCI Express x1, rev. 1
  - 1 x 4 pin power connector
- M.2 interface: SATA / USB, depending on connection cable
- Suitable for M.2 NGFF modules in format: 2280, 2260, 2242 with key B

- or key B+M based on SATA or USB
- mSATA interface: SATA / USB, depending on connection cable
- Attachment for mSATA and MiniPCIe modules can be set to full size or half size
- Operating temperature: 0 °C ~ 70 °C

---

## System requirements

- Windows Vista/Vista-64/7/7-64/8/8-64/8.1/8.1-64
- PC with one free PCI Express slot

---

## Package content

- PCI Express card
- 1 x screw

---

## Images

