

MATERIAL RoHS COMPLIANT:

1.CABLE:
- CONDUCTOR: 30AWG SOLID SILVER PLATED COPPER.
- INSULATION: FOAM POLYOLEFIN.
- PAIR: 2 SINGLES LAID FLAT AND PARALLEL.
- PAIR DRAIN WIRE: 30AWG SOLID TIN PLATED COPPER.
- PAIR SHIELD: ALUMINUM/POLYESTER TAPE. ALUMINUM SIDE FACING IN, 25% OVERLAP.
- DIFFERENTIAL IMPEDANCE: 100±5 OHMS @TDR
- UL RECOGNIZED: AWM STYLE 21490 80°C 30 VOLTS.

2.CONNECTOR:
- P0: Mini SAS 4i 36CKT CONNECTOR.(SFF-8087)
  - (1) HOOD: NYLON, UL94-V0.
  - (2) P.C.B: 4 LAYERS, GOLD PLATING ON CONTACT PADS.
  - (3) LATCH: STAINLESS.
  - (4) INTERNAL, WITH SIDEBAND.
- P1-P4: SATA 7P INTERNAL CABLE REC. WITH LATCH(USAT-F073SL0H).
- P5: 8PIN HOUSING

3.FOR SAS 6.0 Gbps

Date	2018 / 06 / 12
Unit	mm
Projection	
Rev	A

DELOCK we move the world

Title: Cable Mini SAS SFF-8087 > 4 x SATA 7 pin + Sideband 1 m metal

Item no.	85682
Barcode	4043619856824