



MATERIAL RoHS COMPLIANT:

1.CABLE:

CONDUCTOR: 30AWG SOLID SILVER PLATED COPPER.
 INSULATION: FOAM POLYOLEFIN.
 PAIR: 2 SINGLES LAID FLAT AND PARALLEL.
 PAIR DRAIN WIRE: 30AWG SOLID TIN PLATED COPPER.
 PAIR SHIELD: ALUMINUM/POLYESTER TAPE.
 ALUMINUM SIDE FACING IN, 25% OVERLAP.
 DIFFERENTIAL IMPEDANCE: 100±5 OHMS @TDR
 UL RECOGNIZED: AWM STYLE 21490 80°C 30 VOLTS.

2.CONNECTOR:

P1: SFF-8639 68P PLUG CONNECTOR
 (1) P.C.B: 4 LAYERS, GOLD PLATING ON CONTACT PADS
 (2) HOUSING: PVC, BLACK.
 (3) WITHOUT EARS AND SCREWS.
 P2: SFF-8639 68P REC. CONNECTOR
 (1) P.C.B: 4 LAYERS, GOLD PLATING ON CONTACT PADS
 (2) HOUSING: ABS, BLACK.
 (3) WITHOUT EARS AND SCREWS.

3.POWER CABLE:

(1) UL 1007 18AWG*3 80°C 300V
 (2) UL 1007 24AWG*2 80°C 300V

DELCK®
 we move the world

Title: Cable SFF-8639 > SFF-8639

Date	2018 / 10/ 09	Item no.	85738
Unit	mm	Barcode	4043619857388
Projection			
Rev	A		