

PIN ASSEMBLY

P1	1	2	3	4	5	6	7	8	9	64
P2	1	2	3	4	5	6	7	8	9	64
P3	1	2	3	4	5	6	7	8	9	64
	CD	RXD	TXD	DTR	GND	DSR	RTS	CTS	RI	DRIAN

Serial (PC 9)

(At the Computer)

9 PIN D-SUB MALE at the Computer

Pin	Name	Dir	Description
1	CD	←	Carrier Detect
2	RXD	←	Receive Data
3	TXD	→	Transmit Data
4	DTR	→	Data Terminal Ready
5	GND		System Ground
6	DSR	←	Data Set Ready
7	RTS	→	Request to Send
8	CTS	←	Clear to Send
9	RI	←	Ring Indicator

Note: Direction is DTE (Computer) relative DCE (Modem)

No.	Description	Qty
7		
6	COPPER	
5	45P Beige PVC	41g
4	BIG E33 SCREW	6PCS
3	DB 9M (NICKEL PLATED, BLUE INSULATOR)	1PCS
2	DB 9F (NICKEL PLATED, BLUE INSULATOR)	2PCS
1	UL2464 28#*9C+1+AE,OD=5.0mm,BEIGE COLOR,PVC JACKET.	2PCS

Company	Tragant	Goods Code		Draw	何銘鈺	Date	2013.01.14
ITEM NO.		Drawing Evidence		Check		Date	
Goods NO.	DB9M-DB9Fx2			Approval		Date	
Original NO.		Unit(mm)					

Date	2019 / 07 / 09	Title:	Adapter Serial Sub-D9 male > 2 x female 17 cm
Unit	mm	Item no.	65403
Projection		Barcode	4043619654031
Rev	A	File No.	88090

DELOCK
we move the world