



SCALE 1.5/1

## Specification :

### Material :

- Dust Cover : PE, White Color.
- Housing : PC+glassfiber, UL 94V-0.
- Clip : STAINLESS.
- Insert : ABS, UL 94V-0.

### Performance :

- LC Duplex Type.
- Durability : 500 cycles.
- Tensile Strength : 10 kgf.
- Insertion Loss : <0.2 dB(Singlemode)/<0.3 dB(Multimode).
- Operating Temperature: -20°C to +70°C.
- Storage Temperature: -40°C to +80°C.

ITEM NO	Description
<b>86718</b>	Black Insert, LC SM Adaptor With Zr. sleeve, Blue.
	Black Insert, LC SM/APC Adaptor With Zr. sleeve, Green.
<b>86719</b>	Black Insert, LC MM Adaptor With Zr. sleeve, Ivory.
<b>86330</b>	Black Insert, LC MM Adaptor With Zr. sleeve, Lime Green.
<b>86720</b>	Black Insert, LC MM Adaptor With Zr. sleeve, Aqua.
<b>86721</b>	Black Insert, LC MM Adaptor With Zr. sleeve, Violet.

**DELOCK®**  
we move the world

Title: Keystone Module LC Duplex  
to LC Duplex

Date	2021 / 07 / 27	Item no.	<b>86330</b>
Unit	mm	Barcode	4043619863303
Projection		File No.	
Rev	A		