



SCALE 1.5/1

Specification :

Material :

- Dust Cover : PE, White Color.
- Housing : PC+glassfiber, UL 94V-0.
- Clip : STAINLESS.
- Insert : ABS, UL 94V-0.

Performance :

- LC Duplex Type.
- Durability : 500 cycles.
- Tensile Strength : 10 kgf.
- Insertion Loss : <0.2 dB(Singlemode)/<0.3 dB(Multimode).
- Operating Temperature: -20°C to +70°C.
- Storage Temperature: -40°C to +80°C.

ITEM NO	Description
86357	White Insert, LC SM Adaptor With Zr. sleeve, Blue.
	White Insert, LC SM/APC Adaptor With Zr. sleeve, Green.
86347	White Insert, LC MM Adaptor With Zr. sleeve, Ivory.
86816	White Insert, LC MM Adaptor With Zr. sleeve, Lime Green.
86817	White Insert, LC MM Adaptor With Zr. sleeve, Aqua.
86818	White Insert, LC MM Adaptor With Zr. sleeve, Violet.

DELOCK®
we move the world

Title: Keystone Module LC Duplex
to LC Duplex

Date	2021 / 07 / 27	Item no.	86347
Unit	mm	Barcode	4043619863471
Projection		File No.	
Rev	A		