

Delock LTE antena SMA muški 3 - 5 dBi 12 cm, fiksna, višesmjerna s magnetnim postoljem i kabelom za povezivanje RG-174 A/U 3 m vanjska crni

Opis

Ova Delock antena omogućuje vam uporabu različitih LTE opsega na otvorenim i u zatvorenim prostorima.



Predmet br. 12586

EAN: 4043619125869

Zemlja podrijetla: China

Pakiranje: Kutija

Tehnički podaci

- Priključak: 1 x SMA muški
- Frekvencijski opseg:
 - 698 MHz - 960 MHz
 - 1710 MHz - 2170 MHz
 - 2500 MHz - 2700 MHz
- ZigBee, LoRa, DECT, Z-Wave, NB-IoT, Bluetooth, GSM, UMTS, LTE, ISM, WLAN
- Pojačanje antene: 3 - 5 dBi
- Impedancija: 50 ohma
- VSWR: 1,5
- Polarizacija: linearna, vertikalna
- Radna temperatura: -20 °C ~ 70 °C
- Materijal kućišta: plastika
- Boja: crno
- Stupanj zaštite: IPx5
- Kabel: koaksijalni
- Vrsta kabela: RG-174 A/U
- Boja kabela: crna

- Slabljenje kabela: 1,5 dB @ 1,5 GHz po metru
- Promjer kabela: oko 2,7 mm
- Duljina kabela zajedno s priključkom: oko 3 m
- Mjere (DxŠ): oko 120,0 x 50,0 mm




Preduvjeti sustava

- Uređaj sa slobodnim SMA konektorom

Sadržaj pakiranja

- Antena

Slike



General

Mounting type:	magnetic
Protection category:	IPX5
Suitable for outdoor:	Yes (Da)

Interface

priključak:	1 x SMA utikač
-------------	----------------

Technical characteristics

Frequency range:	2500 MHz - 2700 MHz 698 MHz - 960 MHz 1710 MHz - 2170 MHz
Antenna gain:	3 - 5 dBi
Impedancijaa:	50 Ω
Radna temperatura:	-20 °C ~ 70 °C
Polarisation:	linear vertical
VSWR:	1,5

Physical characteristics

Materijal kućišta:	ABS
Cable category:	koaksijalni
Cable type:	RG-174 A/U
Cable attenuation:	1.5 dB @ 1.5 GHz per meter
Boja kabela:	crne
Cable length incl. connector:	3.0 m
Dimensions (LxØ):	120,0 x 50,0 mm