

Delock Antenna Cable N plug > N jack CFD400 LLC400 10 m low loss waterproof

Description

This high-quality coaxial cable ensures a reliable connection of components of the radio frequency technology. It is characterised by a **very low attenuation**. Thanks to the **waterproof** N connector, this cable is ideal for outdoor use.



10 m

Item no. 13029

EAN: 4043619130290

Country of origin: Taiwan,
Republic of China

Package: Box

Technical details

- Connectors:
 - 1 x N plug waterproof >
 - 1 x N jack waterproof
- Impedance: 50 Ohm
- Cable type: CFD400, LLC400
- Cable type: coaxial
- Cable attenuation:
 - 0.30 dB @ 3.0 GHz per meter
 - 0.48 dB @ 6.0 GHz per meter
- Cable diameter: ca. 10.5 mm
- Smallest bending radius: 51.5 mm
- Cable colour: black
- Length incl. connectors (L): ca. 10 m

System requirements

- Device with one free N port


Package content

- Antenna cable

Images



Typ	SWR	f (GHz)	Ref 1 (V)	Cal SWR	SWR	f (GHz)	Ref 1 (V)	Cal SWR
1	1.0000	0.0000	1.0000	1.0000	1	1.0000	0.0000	1.0000
2	1.0000	0.0000	1.0000	1.0000	2	1.0000	0.0000	1.0000
3	1.0000	0.0000	1.0000	1.0000	3	1.0000	0.0000	1.0000
4	1.0000	0.0000	1.0000	1.0000	4	1.0000	0.0000	1.0000
5	1.0000	0.0000	1.0000	1.0000	5	1.0000	0.0000	1.0000
6	1.0000	0.0000	1.0000	1.0000	6	1.0000	0.0000	1.0000
7	1.0000	0.0000	1.0000	1.0000	7	1.0000	0.0000	1.0000
8	1.0000	0.0000	1.0000	1.0000	8	1.0000	0.0000	1.0000
9	1.0000	0.0000	1.0000	1.0000	9	1.0000	0.0000	1.0000
10	1.0000	0.0000	1.0000	1.0000	10	1.0000	0.0000	1.0000
11	1.0000	0.0000	1.0000	1.0000	11	1.0000	0.0000	1.0000
12	1.0000	0.0000	1.0000	1.0000	12	1.0000	0.0000	1.0000
13	1.0000	0.0000	1.0000	1.0000	13	1.0000	0.0000	1.0000
14	1.0000	0.0000	1.0000	1.0000	14	1.0000	0.0000	1.0000
15	1.0000	0.0000	1.0000	1.0000	15	1.0000	0.0000	1.0000
16	1.0000	0.0000	1.0000	1.0000	16	1.0000	0.0000	1.0000
17	1.0000	0.0000	1.0000	1.0000	17	1.0000	0.0000	1.0000
18	1.0000	0.0000	1.0000	1.0000	18	1.0000	0.0000	1.0000
19	1.0000	0.0000	1.0000	1.0000	19	1.0000	0.0000	1.0000
20	1.0000	0.0000	1.0000	1.0000	20	1.0000	0.0000	1.0000
21	1.0000	0.0000	1.0000	1.0000	21	1.0000	0.0000	1.0000
22	1.0000	0.0000	1.0000	1.0000	22	1.0000	0.0000	1.0000
23	1.0000	0.0000	1.0000	1.0000	23	1.0000	0.0000	1.0000
24	1.0000	0.0000	1.0000	1.0000	24	1.0000	0.0000	1.0000
25	1.0000	0.0000	1.0000	1.0000	25	1.0000	0.0000	1.0000
26	1.0000	0.0000	1.0000	1.0000	26	1.0000	0.0000	1.0000
27	1.0000	0.0000	1.0000	1.0000	27	1.0000	0.0000	1.0000
28	1.0000	0.0000	1.0000	1.0000	28	1.0000	0.0000	1.0000
29	1.0000	0.0000	1.0000	1.0000	29	1.0000	0.0000	1.0000
30	1.0000	0.0000	1.0000	1.0000	30	1.0000	0.0000	1.0000



Interface

Connector 1:	N plug
Connector 2:	1 x N female RP-SMA plug

Technical characteristics

Impedance:	50 Ω
------------	------

Physical characteristics

Cable type:	CFD400, LLC400
Cable attenuation:	0.30 dB @ 3.0 GHz 0.48 dB @ 6.0 GHz
Cable colour:	black
Cable length:	10 m
Smallest bending radius:	51.5 mm