

# Delock External Enclosure for M.2 NVMe PCIe SSD with SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ female - tool free

## Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD** in 2280, 2260, 2242 and 2230 format, it can be connected via USB to the PC or laptop. The **robust metal housing with cooling fins** ensures an optimum temperature of the memory.

### SuperSpeed USB 20 Gbps

The enclosure allows a data transfer rate of 20 Gbps on the USB-C™ port.

### SSD installation without tools

The special feature of this enclosure is that no tools are required to install the M.2 SSD.

[External Enclosure for M.2 NVMe](#)

## Note

There is no support for SATA M.2 SSD.



**Item no. 42001**

EAN: 4043619420018

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:  
external: 1 x SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ female  
internal: 1 x 67 pin M.2 key M slot
- Chipset: Asmedia ASM2364
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Data transfer rate up to 20 Gbps
- LED indicator for power and access
- Metal housing

- Dimensions (LxWxH): ca. 119 x 46 x 15 mm
- Hot Plug, Plug & Play

---

## System requirements

- Android 9.0 or above
- Chrome OS 78.0 or above
- Linux Kernel 3.18.37 or above
- Mac OS 10.15.5 or above
- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port

---

## Package content

- External enclosure M.2
- 1 x thermal conductive pad
- Cable USB-C™ male to USB-C™ male, length ca. 30 cm
- User manual

---

## Images



## General

Supported operating system:	Android 9.0 or above Chrome OS 78.0 or above Linux Kernel 3.18.37 or above Mac OS 10.15.5 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

## Interface

External:	1 x USB 20 Gbps USB Type-C™ female
Internal:	1 x 67 pin M.2 key M slot

## Technical characteristics

Chipset:	Asmedia ASM2364
Data transfer rate:	up to 20 Gbps

## Physical characteristics

Housing material:	metal
Length:	119 mm
Width:	46 mm
Height:	15 mm
Colour:	silver