

# Delock 3.5" Mobile Rack for 4 x M.2 NVMe SSD with Slim SAS SFF-8654 connector

## **Description**

This solid metal mobile rack by Delock can be installed into a **3.5"** bay of a PC and provides four M.2 slots in 2280, 2260, 2242 or 2230 format.

### **Quick change of SSD**

Due to the special mechanism, the **SSD** can be exchanged quickly and easily. For example, data backups can be taken and stored in a safe place.

## Tray with key lock and springs

The mobile rack is equipped with a **key lock** to prevent unauthorised access. The stable carrier of metal has springs on the top and bottom which **reduce vibrations** and therefore support its use in mobile devices.

#### Note

Special care must be taken that the tray is fully inserted, otherwise no connection to the SSD can be established.



#### Item no. 47072

EAN: 4043619470723 Country of origin: China

Package: Box

#### Technical details

· Connectors:

Mobile Rack:

internal:

4 x M.2 key M slot

external:

4 x Slim SAS SFF-8654 4i female

4 x 4 pin Floppy male

4 x 2 pin pin header for fan

M.2 tray:

1 x M.2 key M male

1 x M.2 key M slot

• Compatible to PCI Express V4.0

#### DATASHEET



- Interface: PCIe / NVMe
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- 4 x LED indicator
- Bootable, ex UEFI version 2.3.1
- M.2 tray made of metal
- Supports NVM Express (NVMe)
- Supports S.M.A.R.T.
- Key lock
- Dimensions (LxWxH): ca. 159 x 100 x 25 mm

## **System requirements**

- Linux Kernel 6.2 or above
- Windows 10/10-64/11
- Windows Server 2022
- PC with one free 3.5" bay
- A free Slim SAS SFF-8654 port for each M.2 slot
- Power supply with a free SATA power connector

## Package content

- 3.5" Mobile Rack with 4 x M.2 tray
- 2 x cable SATA 15 pin to 2 x 4 pin Floppy female, length ca. 12 cm
- 2 x keys
- 4 x screw I 6.0 x 5.0 mm, head 8.0 mm
- 4 x screw IM 2.0 x 4.0 mm, head 5.0 mm
- User manual



## **Images**















## General

Form factor:	3.5"
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 11 Windows Server 2022 Linux Kernel 6.2 or above

## Interface

External:	4 x Slim SAS SFF-8654 4i female 4 x 4 pin Floppy male 4 x 2 pin pin header for fan
Internal:	4 x M.2 key M slot

## **Physical characteristics**