

# Delock M8 Connector A-coded 4 pin female for mounting with screw connection

## Description

This connector by Delock can be used to connect a cable via a screw terminal connection with an M8 connector, e.g. for machine control or automation.



**Item no. 60532**

EAN: 4043619605323

Country of origin: China

Package: Zip poly bag

## Technical details

- Connectors:
  - 1 x M8 female A-coded 4 pin
  - 4 x screw terminal
- Useable for a cable gauge range from 26 to 22 AWG (0.13 - 0.32 mm<sup>2</sup>)
- Operating voltage: max. 60 V
- Current: max. 3 A
- Operating temperature: -25 °C ~ 85 °C
- Protection class: IP67
- Cable entry max. 3.0 - 4.5 mm
- Thread size: M8 x 1.0 mm
- Housing material: PA66
- Colour: black
- Dimensions (LxD): ca. 42 x 12.1 mm

## System requirements

- A free M8 male port

---

## Package content

- Connector
- Allen key

---

## Images



### Interface

Connector 1:	1 x M8 female
--------------	---------------

### Technical characteristics

Operating voltage:	60 V
Operating temperature:	-25 °C ~ 85 °C
Current consumption:	3 A

### Physical characteristics

Housing material:	Plastic
Pin finishing:	gold-plated
Diameter:	12.1 mm
Length:	42.0 mm
Colour:	black