

Delock Adaptor USB 2.0 Tip-A la 1 x serial RS-232 D-Sub 9 + Adaptor D-Sub 25

Descriere scurta

Acest adaptor de la Delock permite conectarea unui dispozitiv cu interfață serială prin intermediul unui port USB Tip-A.



1,8 m

Nr. 61314

EAN: 4043619613144

Țara de origine: China

Pachet: Retail Box

Detalii tehnice

- Conectori:
 - Cablu:
 - 1 x USB 2.0 Tip-A tată >
 - 1 x RS-232 seriale DB9 tată, cu șuruburi
 - Adaptor:
 - 1 x RS-232 seriale DB9 mamă >
 - 1 x RS-232 seriale DB25 tată
- Chipset: FTDI FT232RL
- Compatibil cu USB 3.0, USB 2.0, și USB 1.1
- Semnale: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Rată de transfer a datelor de până la 460,8 Kbps
- Lungime cablu: aprox. 1,8 m
- Culoare: negru / transparentă

Cerinte de sistem


- Linux Kernel 5.8.0 sau superior

- Mac OS 11.4 sau superior
- Windows 8.1/8.1-64/10/10-64/11
- Windows Server 2016/Windows Server 2019
- PC sau laptop cu un port USB Tip-A liber

Pachetul contine

- USB 2.0 la 1 x seriale adaptoare
- Adaptor DB9 la DB25
- CD cu drivere
- Manual de utilizare

Imagini



General

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 1.1 USB 2.0
Supported operating system:	Linux Kernel 2.6 sau superior Mac OS 10.9 sau superior Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2008 R2 Windows Server 2012 R2 Windows Server 2012 Windows Server 2016 Windows 11

Interface

Conector 1:	1 x USB 2.0 Tip-A tată
Conector 2:	1 x RS-232 seriale DB9, tată

Technical characteristics

Chipset:	FTDI FT232RL
Data transfer rate:	up to 921.6 Kbps
FIFO:	128 byte 256 Byte
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous full duplex
Current consumption:	20 mA
UART:	USB to serial UART

Physical characteristics

Cable colour:	transparentă
Cable length incl. connector:	1,8 m
Pin finishing:	placat cu aur
Tipul șurubului:	#4-40 UNC
Shielding:	double
Colour:	negru