

Delock Adaptor USB 2.0 > 1 x seriale RS-422/485

Descriere scurta

Acest adaptor de la Delock permite conectarea unui dispozitiv cu interfață serială prin intermediul unui port USB Tip-A.



Nr. 62406

EAN: 4043619624065

Țara de origine: China

Pachet: Retail Box

Detalii tehnice

- Conectori:
Adaptor:
1 x USB 2.0 Tip-A tată >
1 x RS-422/485 D-Sub serial 9 pini tată
Bloc de conexiuni:
1 x RS-422/485 D-Sub serial 9 pini mamă >
1 x bloc de conexiuni cu 6 pini
- Chipset: FTDI
- Conector serial cu piulițe
- Rată de transfer a datelor de până la 230,4 Kbps
- Lungime cablu, inclusiv coneciores: cca. 0,8 m

Cerinte de sistem

- Windows Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64/11
- PC sau laptop cu un port USB Tip-A liber

Pachetul contine

- USB 2.0 la 1 x seriale RS-422/485 adaptoare
- Adaptor pentru bloc
- CD cu drivere
- Manual de utilizare

Imagini



62406	D09 Buchse/Female		TerminalBlock/Terminal Block
	RS-422	RS-485	RS-422/RS-485
1	Transmit (A-)	T/R (A-)	T/R (A-)
2	Transmit (B+)	T/R (B+)	T/R (B+)
3	Receive (A-)	NC	Receive (A-)
4	Receive (B+)	NC	Receive (B+)
5	Signal GND (SG)	Signal GND (SG)	Signal GND (SG)
6	NC	NC	NC
7	NC	NC	NC
8	NC	NC	NC
9	NC	NC	NC

General

Function:	Plug & Play
Specification:	RS-422 / RS-485 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 sau superior Mac OS 10.14.1 sau superior Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2012 R2 Windows Server 2012 Windows Server 2016 Windows 11
Protection:	ESD (Electrostatic Discharge)

Interface

Conector 1:	1 x USB 2.0 Tip-A tată
Conector 2:	1 x Serial RS-422/485 DB9 male
connector 3:	1 x bloc de conexiuni cu 6 pini

Technical characteristics

Chipset:	FTDI 232R
Data transfer rate:	bis zu 230,4 Kbps
Data transmission:	asynchronous Semi duplex full duplex differential
UART:	USB to serial UART
Resistor:	Termination resistors 120 Ω
Support:	Modbus

Physical characteristics

Carcasa uitoare:	negru
Material carcasă:	Plastic
Cable colour:	brown transparent
Cable length incl. connector:	0,8 m
Pin finishing:	placat cu aur
Tipul șurubului:	#4-40 UNC
Shielding:	double