

# Delock Adapter USB 2.0 > 1 x seriell RS-422/485

## Beskrivning

Denna adapter från Delock möjliggör anslutning av en seriell enhet via en USB Typ-A-port.



**Artikelnummer 62406**

EAN: 4043619624065

Ursprungsland: China

Paket: Retail Box

## Specifikationer

- Anslutning:  
Adapter:  
1 x USB 2.0 Typ-A hane >  
1 x seriell RS-422/485 D-Sub 9-stifts hane  
Terminalblock:  
1 x seriell RS-422/485 D-Sub 9-stifts hona >  
1 x 6-stifts terminalblock
- Kringkretsar: FTDI
- Seriell kontakt med skruvmuttrar
- Dataöverföringshastighet upp till 230,4 Kbps
- Kabellängd inkl. kontakter: ca. 0,8 m

## Systemkrav

- Windows Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64/11
- Dator eller bärbar dator med en ledig USB Typ-A-port

## Paketets innehåll

- USB 2.0 till 1 x seriell RS-422/485-adapter
- Adapter för terminalblock
- CD-skiva med drivrutiner
- Bruksanvisning

## Bilder



62406	D09 Buchse/Male		TerminalBlock/Terminal Block
	RS-422	RS-485	RS-422/RS-485
1	Transmit (A-)	T/R (A-)	T/R (A-)
2	Transmit (B+)	T/R (B+)	T/R (B+)
3	Receive (A-)	NC	Receive (A-)
4	Receive (B+)	NC	Receive (B+)
5	Signal GND (SG)	Signal GND (SG)	Signal GND (SG)
6	NC	NC	NC
7	NC	NC	NC
8	NC	NC	NC
9	NC	NC	NC

## General

Funktion:	Plug & Play
Specifikationer:	RS-422 / RS-485 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 eller högre Mac OS 10.14.1 eller högre Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2012 R2 Windows Server 2012 Windows Server 2016 Windows 11
Protection:	ESD (Electrostatic Discharge)

## Interface

Kontakt 1:	1 x USB 2.0 Typ-A hane
Kontakt 2:	1 x Serial RS-422/485 DB9 male
kontakt 3:	1 x 6-stifts terminalblock

## Technical characteristics

Kringkretsar:	FTDI 232R
Dataöverföringshastighet:	bis zu 230,4 Kbps
Data transmission:	asynchronous Halv duplex full duplex differential
UART:	USB to serial UART
Resistor:	Termination resistors 120 Ω
Support:	Modbus



## Physical characteristics

Hölje färg:	svart
Höljets material:	Plast
Kabelfärg:	brown transparent
Cable length incl. connector:	0,8 m
Stift slutförda:	guldpläterade
Skruvtyp:	#4-40 UNC
Shielding:	double