

# Delock HDMI Audio Extractor 4K 30 Hz

## Description

This adapter by Delock can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) or analogue (stereo) to other devices, such as headphones or a surround receiver.



**Item no. 62692**

EAN: 4043619626922

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - Input:
    - 1 x HDMI-A 19 pin female
    - 1 x 5 V DC jack 2.1 x 5.5 mm
  - Output:
    - 1 x HDMI-A 19 pin female
    - 1 x 3.5 mm 3 pin stereo jack female (audio)
    - 1 x TOSLINK female S/PDIF
    - 1 x RCA female S/PDIF
- Switchable between stereo and 5.1 channel
- High Speed HDMI, 3D and HDCP 1.4
- Output with HDMI repeater function
- Resolution up to 3840 x 2160 @ 30 Hz (8 bit), 1920 x 1080 @ 60 Hz (12 bit)
- Video bandwidth up to 300 MHz / 3 Gb/s per channel, 9 Gb/s max.
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)
- CEC and HDMI audio routed to the output (pass-through)

- Chipset: CS4344, 24 bit / 192 kHz
- Robust metal housing
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): ca. 71 x 61 x 21 mm

---

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
  - inside:  $\varnothing$  ca. 2.1 mm
  - outside:  $\varnothing$  ca. 5.5 mm
  - length: ca. 9 mm

---

## System requirements

- A free HDMI-A female

---

## Package content

- HDMI Audio Extractor
- Mounting brackets and screws
- USB power cable, length: ca. 0.5 m
- Power supply
- User manual

---

## Images



## General

Specification:	DTS Audio High Speed HDMI Dolby Digital HDCP 1.4 LPCM
----------------	---

## Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 1 x RCA female 1 x HDMI-A female 1 x TOSLINK female
Input:	1 x HDMI-A female 1 x 5 V DC female 5,5 mm x 2,1 mm

## Technical characteristics

Chipset:	Cirrus CS4344
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Video bandwidth:	300 MHz

## Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	71 mm
Width:	61 mm
Height:	21 mm

## Power supply

Type:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.3 A
Output:	5 V / 1 A

Connector:	DC male 5.5 mm x 2.1 mm
Cable length:	1 m