

Prilagodnik USB 2.0 Tip-A > 1 x serijski DB9 RS-232 kutni 110°

Opis

Ovaj USB Tip-A na serijski adapter tvrtke Delock omogućava RS-232 ulaz za mjerače, POS sustave, pisače, modeme, IoT uređaje, itd.



Predmet br. 63916

EAN: 4043619639168

Zemlja podrijetla: China

Pakiranje: Retail Box

Tehnički podaci

- Priključak:
 - 1 x USB 2.0 Tip-A muški >
 - 1 x serijska muška RS-232 DB9
- Skup čipova: Prolific PL2303 HXD
- Vrsta vijka: #4-40 UNC
- Kompatibilan s USB 2.0, i USB 1.1 pune brzine 12 Mbps
- Brzina prijenosa podataka do 460,8 Kbps
- LED indikator
- Signali: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Paritet parni, neparni, nijedan, oznaka, prazno mjesto
- Stop bit: 1, 1,5, 2
- Podatkovni bit: 5, 6, 7, 8
- Kontrola protoka: nema, Xon/Xoff, RTS/CTS
- FIFO: 512 bajtni međuspremnik dvosmjerni



Preduvjeti sustava

- Windows 7/7-64/8.1/8.1-64/10/10-64, ex Linux Kernel 2.6, ex Mac OS 10.9
- Osobno ili prijenosno računalo sa slobodnim USB Tipa-A priključkom

Sadržaj pakiranja

- USB 2.0 na 1 x serijski adapter
- CD s upravljačkim programom
- Korisnički priručnik

Slike



General

Funkcija:	Plug & Play
Tehnički podaci:	RS-232 (EIA / TIA) USB 1.1 USB 2.0
Supported operating system:	Linux Kernel 3.3 ili noviji Mac OS 10.12 ili noviji Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

Priključak 1:	1 x USB 2.0 Tipa-A muški
Priključak 2:	1 x serijska muška RS-232 DB9

Technical characteristics

Skup čipova:	Prolific PL2303HXD
Brzina prijenosa podataka:	up to 460,8 Kbps
FIFO:	512 byte
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous full duplex
Napon:	USB Bus powered (no additional power supply required)

Physical characteristics

Cable length incl. connector:	1,8 m
Vrsta vijka:	#4-40 UNC
Boja:	crne