

Delock External USB 3.2 Hub 4 Port with 10 Gbps

Description

This USB hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by **four USB Type-A** connectors.

Hub with power supply

The included power supply provides power to the connected devices on the front. The hub can also be used without a power supply.



Item no. 64053

EAN: 4043619640539 Country of origin: China Package: Retail Box

Technical details

Connectors:

1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C[™] female 4 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female 1 x DC 12 V power connector

- Chipset: VIA VL822
- Data transfer rate up to: SuperSpeed USB 10 Gbps, SuperSpeed USB 5 Gbps, Hi-Speed 480 Mbps, Full-Speed 12 Mbps, Low-Speed 1.5 Mbps
- 1 x LED indicator
- Colour: black
- Dimensions (LxWxH): ca. 92 x 54 x 19 mm
- Plug & Play

Power supply specification

· Wall power supply

DATASHEET



- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions: inside: ø ca. 2.5 mm outside: ø ca. 5.5 mm length: ca. 10 mm

System requirements

- Chrome OS
- Linux Kernel 4.6 or above
- Mac OS 10.13.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- Hub USB
- 1 x Cable USB A male to USB-C[™] male, length ca. 1 m
- Power supply
- User manual

Images



DATASHEET



General

Function:	Plug & Play
Specification:	USB 10 Gbps
Supported operating system:	Chrome OS Linux Kernel 4.6 or above Mac OS 10.13.3 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11
LED indicator:	1 x

Interface

Connector 1:	1 x USB 10 Gbps USB Type-C™ female
Connector 2:	4 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female
connector 3:	1 x DC jack

Technical characteristics

Chipset:	VIA VL822
Data transfer rate:	10 Gbps

Physical characteristics

Length:	92 mm
Width:	54 mm
Height:	19 mm
Colour:	black

Power supply

DATASHEET



Input:	AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
Output:	12 V / 2 A
Connector:	DC plug 5.5 mm x 2.5 mm