

# Delock USB Type-C<sup>™</sup> Adapter to Gigabit LAN 10/100/1000 Mbps with Power Delivery port white

#### Description

The adapter by Delock expands a PC or laptop by one **network** interface via the USB Type-C<sup>™</sup> interface. In addition, the adapter can also be operated on a Thunderbolt<sup>™</sup> 3 interface.

# USB Power Delivery (USB PD 2.0) support up to 60 watt

The adapter has a USB Type-C<sup>™</sup> Power Delivery port to connect the power supply of the laptop to charge it. The adapter can also be used without a power supply.



#### Item no. 65402

EAN: 4043619654024 Country of origin: China Package: Retail Box

### **Technical details**

- Connectors:
  - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C<sup>™</sup> male >
  - 1 x Gigabit LAN RJ45 jack
  - 1 x USB Type-C<sup>™</sup> PD female (power supply)
- Chipset: Realtek RTL8153, VIA VL100
- SuperSpeed USB 5 Gbps specification
- Data transfer rate:
- Ethernet up to 10 Mbps (Half/Full Duplex) Fast Ethernet up to 100 Mbps (Half/Full Duplex) Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)
- Compatible with: IEEE 802.3: 10BASE-T IEEE 802.3u: 100BASE-TX IEEE 802.3ab: 1000BASE-T
- Supports Auto MDI-X (automatic detection of standard or crossover network cable)
- Supports Wake On LAN (WOL)
- Supports IEEE 802.3az (Energy Efficient Ethernet)
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation

#### **DATASHEET**



with back-pressure flow control

- Supports 9k Jumbo Frames
- Output power for host: max. 60 W
- LED indicator for power and activity
- USB bus powered
- Colour: white
- Cable length incl. connectors: ca. 11.5 cm

#### System requirements

- Android 9.0 or above
- Chrome OS 78.0 or above
- iPad Pro (2018)
- Linux Kernel 3.18 or above
- Mac OS 10.15.3 or above
- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-C<sup>™</sup> port or with a free Thunderbolt<sup>™</sup> 3 port

#### Package content

- USB Type-C<sup>™</sup> Gigabit LAN adapter
- User manual

#### Images





#### General

Supported operating system:	Android 9.0 or above Chrome OS 78.0 or above Linux Kernel 3.18 or above Mac OS 10.15.3 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018)
LED indicator:	2 x

#### Interface

Connector 1:	1 x USB 5 Gbps USB Type-C™ male
Connector 2:	1 x Gigabit LAN RJ45 jack
connector 3:	1 x USB Type-C <sup>™</sup> Power Delivery female

#### **Technical characteristics**

Chipset:	Realtek RTL8153 VIA VL100
Data transfer rate:	Gigabit Ethernet up to 100 Gbps Gigabit Ethernet up to 10 Gbps Gigabit Ethernet up to 1000 Mbps

## **Physical characteristics**

|--|