

Delock USB Microphone with base and Touch-Mute Button

Description

This USB microphone by Delock can be used for voice and vocal transmissions. The rubberized base provides a non-slip stand and the gooseneck allows the microphone to bend in the ideal direction. The LED ring indicates that the microphone is ready for operation by means of a blue or red light and the touch mute button can be used to mute the microphone.



Item no. 65868

EAN: 4043619658688

Country of origin: China

Package: Retail Box

Technical details

- Connector: 1 x USB 2.0 Type-A reversible male
- Sensitivity: -37 dB +/- 3 dB
- Frequency range: 70 Hz - 15 kHz
- Impedance: 2.2 kOhm +/- 30% at 1 kHz
- Sample rate: 16 Bit / 48 kHz
- Touch Mute-Button
- Gooseneck
- Status LED
- Rubber Base
- Colour: black
- Cable length: ca. 1.7 m
- Dimensions (LxWxH): ca. 140 x 60 x 60 mm
- USB bus powered
- Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Images



General

| | |
|-----------------------------|---|
| Function: | Plug & Play |
| Supported operating system: | Linux Kernel 3.3 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit |

Interface

| | |
|------------|------------------------------------|
| connector: | 1 x USB 2.0 Type-A reversible male |
|------------|------------------------------------|

Technical characteristics

| | |
|------------------|---|
| Frequency range: | 70 Hz - 15 kHz |
| Impedance: | 2.2 kOhm +/- 30% at 1 kHz |
| Voltage: | USB Bus powered (no additional power supply required) |
| Sensibility: | -37 dB +/- 3 dB |
| Sample rate: | 16 Bit / 48 kHz |

Physical characteristics

| | |
|---------------|--------|
| Cable length: | 1.7 m |
| Length: | 140 mm |
| Width: | 60 mm |
| Height: | 60 mm |
| Colour: | black |