

# Delock USB Microphone with Gooseneck and Mute Button

## Description

This USB microphone by Delock can be used for voice and vocal transmissions.

### Optimal recordings

The microphone has a cardioid polar pattern (unidirectional) and captures the sound ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

### Mute button & LED ring

With the mute button in the middle of the microphone, the microphone can be quickly muted. The LED ring signals operational status with a blue or red light.

### Flexible gooseneck

With the gooseneck, the microphone can be bent in the preferred direction.

### Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.



**Item no. 66499**

EAN: 4043619664993

Country of origin: China

Package: Retail Box

## Technical details

- Connector: 1 x USB 2.0 Type-A male
- Directivity: unidirectional
- Sensitivity: -35 dB +/- 3 dB
- Frequency range: 70 Hz - 15 kHz
- Sample rate: 16 Bit / 48 kHz
- Mute-Button
- Gooseneck, length ca. 7 cm

- Status LED
  - Dimensions (LxWxH): ca. 196 x 23 x 23 mm
  - USB bus powered
  - Plug & Play
- 

## System requirements

- Chrome OS
  - Linux Kernel 3.3 or above
  - Mac OS 10.9 or above
  - Windows 8.1/8.1-64/10/10-64
  - PC or laptop with a free USB Type-A port
- 

## Package content

- USB microphone
  - User manual
- 

## Images



## General

Function:	Plug & Play
Specification:	USB 2.0
Supported operating system:	Chrome OS Linux Kernel 3.3 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	1 x

## Interface

connector:	1 x USB 2.0 Type-A male
------------	-------------------------

## Technical characteristics

Frequency range:	70 Hz - 15 kHz
Voltage:	USB bus powered
Sensibility:	-35 dB +/- 3 dB
Sample rate:	16 Bit / 48 kHz
Directivity:	uni-directional

## Physical characteristics

Length:	196 mm
Width:	23 mm
Height:	23 mm
LED colour:	red blue