

Delock Adapter USB Type-A male to 2.5 Gigabit LAN compact

Description

The adapter by Delock expands a PC or laptop by **one network interface** via the **USB Type-A** interface.

NBASE-T for higher speed

Modern services and new technologies require higher bandwidths. NBASE-T technology enables speeds of 1 Gbps and **2.5 Gbps** with conventional networking cables. The best possible transmission rate is set automatically.



Item no. 66646

EAN: 4043619666461 Country of origin: China Package: Retail Box

Technical details

- Connectors:
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A male >
 - 1 x 2.5 Gigabit LAN RJ45 jack
- Chipset: Realtek RTL8156
- SuperSpeed USB 5 Gbps specification
- Data transfer rate:

Ethernet up to 10 Mbps (Half/Full Duplex)

Fast Ethernet up to 100 Mbps (Half/Full Duplex)

Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)

NBASE-T with up to 2.5 Gbps (Half/Full Duplex)

- Supports Auto MDI-X (automatic detection of standard or crossover network cable)
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation with back-pressure flow control
- · LED indicator for link and activity
- USB bus powered
- Colour: black
- Dimensions (LxWxH): ca. 53 x 22 x 15 mm
- · Cable length without connectors: ca. 16 cm





System requirements

- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-A female port

Package content

- USB Type-A 2.5 Gigabit LAN adapter
- User manual

Images









General

Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	power and activity

Interface

Connector 1:	1 x USB 5 Gbps Type-A male
Connector 2:	1 x Gigabit LAN RJ45 jack

Technical characteristics

Chipset:	Realtek RTL8156
Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps Gigabit Ethernet up to 2.5 Gbps

Physical characteristics

Housing material:	Plastic
Cable length:	16 cm
Length:	53 mm
Width:	22 mm
Height:	15 mm
Colour:	black