

Delock PoweredUSB cable male 24 V to Mini-DIN 3 pin male 1 m for POS printers and terminals

Description

This PoweredUSB cable by Delock can be used to supply power to a device with Mini-DIN female port via a PC or hub with PoweredUSB 24 V port.



1 m

Item no. 85945

EAN: 4043619859450

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x PoweredUSB male 24 V >
 - 1 x Hosiden Mini-DIN 3 pin power male
- PoweredUSB specification
- Voltage: 24 V
- Cable gauge: 22 AWG
- Cable diameter: ca. 5 mm
- Cable double shielded
- Colour: black
- Length incl. connectors: ca. 1 m

System requirements

- PC or hub with a free PoweredUSB 24 V female port
- Device with a free Hosiden Mini-DIN 3 pin power female port

Package content

- PoweredUSB cable

Images



General

Specification:	PoweredUSB
----------------	------------

Interface

Connector 1:	1 x PoweredUSB male 24 V
Connector 2:	1 x Hosiden Mini-DIN 3 pin male

Technical characteristics

Voltage:	24 V
----------	------

Physical characteristics

Conductor gauge:	22 AWG
Shielding:	double
Length:	1 m
Colour:	black