

Delock Serijski kabel RS-232 D-Sub9 muški na ženski 5 m

Opis

Ovaj serijski kabel tvrtke Delock prikladan je kao produžni kabel ili spojni kabel za modem, pisač, mjerne instrumente, pretvarače, RS232 koncentratore, patch panele, itd. Kabel omogućava spajanje susjednih sustava i uređaja.

Mini D-Sub9 spojnik

Ovi kabeli pristaju svakom ulazu tipa RS-232, jer su mini D-Sub9 (44 x 33,3 x 15 mm) spojnici maleni i kompaktni. Tako se RS-232 spojnici mogu koristiti odmah jedan pored drugog.



5 m

Predmet br. 86598

EAN: 4043619865987

Zemlja podrijetla: China

Pakiranje: Plastična vrećica sa zip zatvaračem

Tehnički podaci

- Priključak:
 - 1 x serijska muška D-Sub9 s vijcima >
 - 1 x serijska ženski D-Sub9 s vijcima
- Presjek kabela: 28 AWG
- Dodjeljivanje pinova: 1:1
- Boja: crno
- Izolator: PVC
- Vrsta vijka: #4-40 UNC
- Promjer kabela: oko 5 mm
- Duljina kabela zajedno s priključkom: oko 5 m

Preduvjeti sustava

- Jedan slobodan D-Sub9 ženski
- Slobodan D-Sub9 muški priključak.

Sadržaj pakiranja

- Kabel

Slike



General

| | |
|------------------|------------------------------|
| Tehnički podaci: | RS-232 (EIA / TIA) |
| Style: | Connection- / Extensioncable |

Interface

| | |
|---------------|---------------------------------------|
| Priključak 1: | 1 x serijska muška Sub-D 9 s vijcima |
| Priključak 2: | 1 x serial Sub-D 9 female with screws |

Technical characteristics

| | |
|----------------------------|--|
| Brzina prijenosa podataka: | up to 921.6 Kbps |
| Signal transmission: | TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND |

Physical characteristics

| | |
|-------------------------------|--|
| Cable type: | AWM Style 2464 28 AWG 80 °C 300 V VW-1 |
| Cable length incl. connector: | 5 m |
| Površinska zaštita kontakata: | pozlaćeni |
| Conductor material: | Copper tinned |
| Conductor gauge: | AWG 28 |
| Vrsta vijka: | #4-40 UNC |
| Shielding: | Aluminum foil |
| Boja: | crne |
| Cable jacket material: | PVC |