

# Delock USB Type-C™ Triple Display Docking Station with DisplayLink® 4K / USB 5 Gbps / LAN / SD / Audio / PD 80 W

## Description

This docking station by Delock can be connected to a computer with a USB-C™ DP Alt Mode, Thunderbolt™ 3 or Thunderbolt™ 4 and provides a variety of interfaces. **Three monitors** can be operated at the monitor outputs **at the same time**. Five built-in USB 5 Gbps ports allow the use of peripherals and another USB port can be used to charge mobile devices. Connectors for a headset, a Gigabit network connection, as well as a card reader for SD and Micro SD memory cards complete the features. A safety cable can be attached to the Kensington socket to protect the docking station from theft.

## Triple Display 4K UHD resolution

When using the three video outputs at the same time, **one monitor is operated via DisplayPort Alternate Mode**, the **other two via DisplayLink®**. The Delock docking station can also be operated on devices without a USB Type-C™ port with DP Alt Mode support, with a video output on a maximum of two monitors.

A maximum resolution of **4K on all ports** can be guaranteed, regardless of the operating system. Due to the DisplayLink® graphics chipset it is possible to use **mirrored and extended screen functions on Windows and Mac OS** operating systems.

## USB Power Delivery (USB PD 3.0) support up to 80 watt

Via the power supply, which is connected to the docking station, the host device is charged with up to **80 watts** during operation.

## Use under the laptop

Due to its elongated, slim shape, the docking station is perfectly suited for use **under a laptop**, e.g. MacBook. The increased tilt of the laptop serves a better comfort while working, as well as a better cooling of the laptop.



**Item no. 88050**

EAN: 4043619880508

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x USB Type-C™ female
  - 1 x DisplayPort female (DisplayLink®)
  - 1 x HDMI female (DisplayLink®)
  - 1 x HDMI female (DP Alt Mode)
  - 4 x USB 5 Gbps Type-A female
  - 1 x USB 5 Gbps USB Type-C™ female
  - 1 x USB Type-A female 5 V / 2.4 A - Battery Charging specification BC1.2
  - 1 x Headset 3.5 mm 4 pin jack
  - 1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack
  - 1 x SD slot
  - 1 x Micro SD slot
  - 1 x DC 20 V power connector
- Maximum resolution (depending on the system and the connected hardware):

Host Type-C™ DP Alt Mode:

|                | HDMI 1 (DP Alt mode) | HDMI 2 (Displaylink) | DisplayPort (Displaylink) |
|----------------|----------------------|----------------------|---------------------------|
| Single Display | 4K / 30 Hz           | -                    | -                         |
|                | -                    | 4K / 60 Hz           | -                         |
|                | -                    | -                    | 4K / 60 Hz                |
| Dual Display   | 4K / 30 Hz           | 4K / 60 Hz           | -                         |
|                | 4K / 30 Hz           | -                    | 4K / 60 Hz                |
|                | -                    | 4K / 60 Hz           | 4K / 60 Hz                |
| Triple Display | 4K / 30 Hz           | 4K / 60 Hz           | 4K / 60 Hz                |

Host without DP Alt Mode:

|                | HDMI 1 (DP Alt mode) | HDMI 2 (Displaylink) | DisplayPort (Displaylink) |
|----------------|----------------------|----------------------|---------------------------|
| Single Display | -                    | 4K / 60 Hz           | -                         |
|                | -                    | -                    | 4K / 60 Hz                |
| Dual Display   | -                    | 4K / 60 Hz           | 4K / 60 Hz                |

- Transmission of audio and video signals
- Functions: Mirrored or Extended
- It can be used two memory cards at the same time
- Input power: 120 W, 40 W are used for the docking station
- Output power for host: max. 80 W
- 1 x LED indicator
- 1 x On / Off switch
- Colour: black
- Security lock (Kensington Lock) for security cable
- Dimensions (LxWxH): ca. 304 x 76 x 19 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2.0 A
- Output: 20 V / 6.0 A / 120 W
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 3.0 mm
  - outside: ø ca. 4.5 mm

length: ca. 10.0 mm

## System requirements

- Mac OS 12.4 or above
- Windows 10/10-64/11
- A free USB Type-C™ female port (DisplayLink®) or
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port

## Package content

- USB docking station
- Cable USB-C™ male to USB-C™ male, length ca. 1 m
- Power supply, cable length ca. 1.2 m
- Power cord, length ca. 1.2 m
- User manual

## Images



## General

|                             |  |
|-----------------------------|--|
| Function:                   | mirror and extend  |
| Supported operating system: | Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 11<br>Mac OS 12.4 oder höher |

## Technical characteristics

|                            |                     |
|----------------------------|---------------------|
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz |
|----------------------------|---------------------|

## Physical characteristics

|         |        |
|---------|--------|
| Length: | 304 mm |
| Width:  | 76 mm  |
| Height: | 19 mm  |
| Colour: | black  |