

Delock LTE antena SMA utikač 0,1 - 4,5 dBi višesmjerni s crni nagibnim spojem

Opis

Antena za GSM / UMTS / LTE može se spojiti na GSM / UMTS / LTE uređaj sa SMA sučeljem radi slanja i primanja signala.



Predmet br. 88436

EAN: 4043619884360

Zemlja podrijetla: Taiwan,
Republic of China

Pakiranje: Retail Box

Tehnički podaci

- Priključak: SMA utikač
- Frekvencijski opseg:
 - 791 - 894 MHz
 - 1920 - 2170 MHz
- Pojačanje antene:
 - 0,1 - 1,2 dBi @ 791 - 894 MHz
 - 3,0 - 4,5 dBi @ 1920 - 2170 MHz
- Impedancija: 50 ohma
- Polarizacija: linearna, vertikalna
- VSWR: 3,0
- Radna temperatura: -10 °C ~ 55 °C
- Materijal kućišta: ABS
- Boja: crno
- Duljina:
 - oko 296,10 mm (s nagibnim spojem)
 - oko 245,00 mm (bez nagibnog spoja)
- Promjer:
 - oko 24,00 mm (gornji)

oko 28,50 mm (maks)
oko 13,50 mm (SMA)



Preuvjeti sustava

- Uređaj sa slobodnim SMA utičnicom

Sadržaj pakiranja

- LTE antena

Slike



General

Suitable for indoor:	Yes (Da)
----------------------	----------

Interface

priključak:	SMA Stecker
-------------	-------------

Technical characteristics

Frequency range:	1920 - 2170 MHz 791 - 894 MHz
Gain:	0,1 - 1,2 dBi @ 791 - 894 MHz 3,0 - 4,5 dBi @ 1920 - 2170 MHz
Impedancijaa:	50 Ω
Radna temperatura:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	3,0

Physical characteristics

Materijal kućišta:	ABS
Diameter connector:	13,50 mm
Duljina s nagibnim spojem:	296,10 mm
Duljina bez nagibnog spoja:	245,00 mm
Boja:	crne