

Delock PCI Express x1 Card to 1 x 2.5 Gigabit LAN PoE+ i225

Description

The PCI Express card by Delock offers one network port with a data transfer rate up to 2500 Mbps.

NBASE-T for higher speed

Modern services and new technologies require higher bandwidths. NBASE-T technology enables speeds of 1 Gbps and 2.5 Gbps with conventional networking cables. The best possible transmission rate is set automatically.



The RJ45 port supports Power over Ethernet according to IEEE 802.3af / 802.3at, so power can be supplied to PoE-enabled devices, such as IP cameras or PoE splitters via the network cable.



Item no. 88506

EAN: 4043619885060 Country of origin: China

Package: Box

Technical details

· Connectors:

external:

1 x 2.5 Gigabit LAN RJ45 jack

internal:

1 x PCI Express x1, V2.1

1 x SATA 15 pin power connector

- Chipset: Intel i225V
- Data transfer rate:

Ethernet up to 10 Mbps (Half/Full Duplex)

Fast Ethernet up to 100 Mbps (Half/Full Duplex)

Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)

NBASE-T with up to 2.5 Gbps (Half/Full Duplex)

PCI Express x1 up to 2.5 Gbps

- Supports IEEE 802.3 / 802.3u / 802.3ab
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Supports Wake On LAN (WOL)
- Supports 9k Jumbo Frames



• Supports PXE

- Supports IEEE 802.3af PoE
- Supports IEEE 802.3at PoE+
- Phantom power (Mode B, pairs 4/5 and 7/8)
- Output power: max. 30 W total
- LED indicator for link and activity

System requirements

- Windows 10/10-64/11
- PC with one free PCI Express slot

Package content

- PCI Express card
- · Low profile bracket
- User manual

Images









General

Supported operating system: Linux Kernel 5.8.0 or above

Windows 10 32-Bit Windows 10 64-Bit

Windows 11

Interface

External: 1 x Gigabit LAN RJ45 jack

Internal: 1 x PCI Express x1, V2.1

Technical characteristics

Chipset:

Intel® i225V v3

Data transfer rate:

Ethernet up to 10 Mbps
Fast Ethernet up to 100 Mbps
Gigabit Ethernet up to 1 Gbps
Gigabit Ethernet up to 2.5 Gbps

Physical characteristics

Slot bracket: Low Profile

standard