

Delock PCI Express x4 Card to 3 x USB Type-C™ + 2 x USB Type-A - SuperSpeed USB 10 Gbps

Description

This PCI Express card by Delock expands the PC by **five external USB 3.2 ports**. Different USB devices, such as docking stations, card readers, external enclosures etc., can be connected to the card.

Sufficient ports - 3 x USB Type-C[™] and 2 x USB Type-A

The PCIe card offers three USB-CTM port as well as two USB Type-A ports. Thus devices can be connected with **10 Gbps** at each port.



Item no. 89074

EAN: 4043619890743 Country of origin: China

Package: Box

Technical details

Connectors:

external:

3 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female

2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female internal:

1 x PCI Express x4 (2-Lane), V3.0

1 x SATA 15 pin power connector

- Chipset: Asmedia ASM3142, VIA VL822
- Data transfer rate up to:

SuperSpeed USB 10 Gbps,

SuperSpeed USB 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

- Downwards compatible to USB 3.0, USB 2.0, USB 1.1
- Power supply via SATA power connector
- · Electrical power:

USB Type-CTM: max. 15 watt (5 V / 3 A)

USB Type-A: max. 4.5 watt (5 V / 0.9 A)





- Bootable
- Supports UASP
- Supports eXtensible Host Controller Interface (xHCI) specification 1.1
- Supports Multiple INs
- Operating temperature: 5 °C ~ 50 °C
- Storage temperature: -20 °C ~ 60 °C
- Humidity: 20 ~ 80 %

System requirements

- Linux Kernel 3.18.37 or above
- Windows 10/10-64/11
- Windows Server 2016
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Package content

- PCI Express card SuperSpeed USB 10 Gbps
- User manual

Images







General

Function:	bootable
Supported operating system:	Linux Kernel 3.18.37 or above Windows 10 32-Bit Windows 10 64-Bit Windows 11

Interface

External:	3 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C [™] female 2 x USB 10 Gbps Type-A female
Internal:	1 x PCI Express x4, V3.0 1 x SATA 15 pin power connector

Technical characteristics

Chipset:	Asmedia ASM3142 VIA VL822
Data transfer rate:	10 Gbps