

# Delock PCI Express x1 Kartica na 8 x serijski RS-232

## Opis

PCI Express kartica tvrtke Delock nadograđuje računalo osam serijskim RS-232 ulazima. Na ovu karticu mogu se spojiti razni uređaji, primjerice skener, konverter protokola, IoT uređaj, itd.

### Fanout kabel

Približno 45 cm dug fanout kabel omogućava visoki stupanj prilagodljivosti na osam RS-232 ulaza te pojednostavljuje rukovanje računalima, strojevima, sustavima, itd.



0°C  +70°C

### Predmet br. 90411

EAN: 4043619904112

Zemlja podrijetla: China

Pakiranje: Retail Box

## Tehnički podaci

- Priključak:
  - vanjski:
    - 1 x DB62 ženski
    - kabel za spajanje: DB62 muški > 2 serijska muška priključka RS-232 DB9
  - unutarnji:
    - 1 x PCI Express x1, V1.1
- Skup čipova: SystemBase 16C1058PCI
- Kompatibilno s 16C550 UART
- Brzina prijenosa podataka do 921,6 Kbps
- FIFO: 8 x 256 bajta
- Podatkovnih bitova: 5, 6, 7, 8
- Stop bitova: 1, 1,5, 2
- Paritet parni, neparni, nijedan, oznaka, prazno mjesto
- Kontrola protoka: nema, hardver RTS / CTS, softver XON / XOFF
- Radna temperatura: 0 °C ~ 70 °C
- Duljina kabela zajedno s priključkom: oko 45 cm
- Mjere (DxŠxV): oko 93 x 78 x 12 mm


## Preduvjeti sustava

- Windows 7/7-64/8.1/8.1-64/10/10-64
- Računalo s jednim slobodnim PCI Express utorom

## Sadržaj pakiranja

- PCI Express kartica
- 1 serijski spojni kabel
- CD s upravljačkim programom
- Korisnički priručnik

## Slike



## General

Tehnički podaci:	RS-232 (EIA / TIA) PCIe 1.1
Supported operating system:	Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Slot:	PCIe

## Interface

Vanjski:	8 x Serial RS-232 DB9 Plug 1 x Sub-D 62 Pin
Unutarnji:	1 x PCI Express x1, V1.1

## Technical characteristics

Skup čipova:	SystemBase 16C1058PCI
Brzina prijenosa podataka:	up to 921.6 Kbps bis zu 8 x 230,4 kbps
FIFO:	8 x 256 Byte
Radna temperatura:	0 °C ~ 70 °C
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous Bi-directional full duplex
UART:	16C550
Support:	Modbus
Data bits:	5, 6, 7, 8

## Physical characteristics

Cable type:	AWM Style 2464 30 AWG 80 °C 300 V VW-1
Boja kabela:	crne
Cable length incl. connector:	45 cm
Vrsta vijka:	#4-40 UNC
Materijal:	PVC
Boja:	zeleno